

ECONOMY LINE

5 Mpix Bullet Camera

LTV CNE-650 48

Article No.: 22700004





Main Features:

- 5 megapixel resolution (2592x1944)
- day/night (ICR)
- IR illumination up to 50 m
- 3D DNR, Digital WDR
- CVBS video output and 2-way audio
- H.265 video compression
- Gigabit ethernet network port
- PoE
- remote access via apps



Accessories:

Picture	Article No.	Model
	42300009	LTV-BMW-JB5-E
	42300012	LTV-BMW-JB3-E

Camera	
Image Sensor	1/1.8" CMOS
Effective Pixels (HxV)	2592x1944
Electronic Shutter Speed	1/25s ~ 1/100000s
Min. Illumination	0.01 Lux @F1.2, AGC on; 0 Lux with IR
Lens	
Focal Length	3.6 - 10 mm (F=1.4)
Lens	Varifocal lens
FOV	83.7°- 36.7°
Video	
Compression	H.265 / H.264 / MJPEG
Resolution	5MP (2592x1944), 2K (2560x1440), 1080P (1920x1080), 720P (1280x720), D1, CIF, 480x240
Framerate	Main Stream 60Hz: 5MP (1~30fps) / 2K (1~30fps) / 1080P (1~30fps) / 720P (1~30fps) 50Hz: 5MP (1~25fps) / 2K (1~25fps) / 1080P (1~25fps) / 720P (1~25fps)
Bitrate	64 Kbps ~ 10 Mbps
Function	
IR Lights	50 m
Day/Night	ICR
Backlight Compensation	Digital WDR
Noise Reduction	2D / 3D DNR
Audio	1x Mic In, 1x Mic Out
Audio Compression	G.711A / U
Video Output	CVBS Video Output (1x BNC)
Alarm I/O	1x CH Input / 1x CH Output
Micro SD	Max. 64 GB
PTZ	1x RS485
Network	
Network	1x RJ45 Gigabit ethernet network port, 10M/100M/1000M self-adaptive
Protocols	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Interface Protocols	ONVIF, GB-T / 28181-2011
Web Viewer	Internet Explorer
Miscellaneous	
Power Supply	DC 12V / PoE
Power Consumption	<3W
Operating Temperature	-20°C ... +50°C, 10% ~ 90% humidity
Protection Class	IP66
Dimensions	Ø 109 x 284 mm
Weight	1.13 kg