

## 4-Channel Triplex DVR with 1TB HDD incl.

LTV-DVR-0461-HV



- 4-channel triplex DVR
- 4 audio inputs / 1 output
- H.264
- resolution and recording speed: 960H/ CIF/ 2CIF/ 4CIF: 25 fps/ channel
- 3 monitor outputs (BNC+VGA+HDMI)
- 1TB HDD incl.
- 2xUSB
- motion detector
- 4 alarm inputs/ 1 output
- telemetry
- Ethernet
- Power supply 12V (DC), 10W (less HDD)

|                    |                          |  |
|--------------------|--------------------------|--|
| Video/audio input  | Video input              | 4xBNC (1.0Vp-p, 75Ω) PAL/NTSC  |
|                    | Audio input              | 4xRCA (2.0Vp-p, 1kΩ)   |
|                    | Two-way audio input      | 1xRCA (2.0Vp-p, 1kΩ)   |
| Video/audio output | BNC output               | 1xBNC (1.0 Vp-p, 75 Ω)   |
|                    | BNC resolution           | PAL: 704x576; NTSC: 704x480  |
|                    | HDMI/VGA output          | 1 HDMI & 1 VGA   |
|                    | HDMI/VGA resolution      | 1920×1080P / 60 Hz, 1600×1200 / 60 Hz, 1280×1024 / 60 Hz, 1280×720 / 60 Hz, 1024×768 / 60 Hz |
|                    | Loop output              | -  |
|                    | Audio output             | 1xRCA (2.0Vp-p, 1KΩ)   |
| Recording          | Video compression        | H.264  |
|                    | Audio compression        | G.711  |
|                    | Stream type              | Video / Video end audio  |
|                    | Frame rate               | WD1/4CIF/2CIF/CIF/QCIF; PAL:1/16—25fps, NTSC: 1/16—30fps                                     |
|                    | Video bit rate           | 32...3072Kbps / or user defined, max 3072 Kbps   |
|                    | Audio bit rate           | 64 Kbps  |
|                    | Dual stream              | Support; Sub-stream: CIF ,QCIF 25k/c   |
|                    | Synchronous playback     | 4 ch   |
| HDD                | SATA                     | 1xSATA   |
|                    | Capacity                 | Up to 4TB capacity   |
| Interface          | Network                  | 1xRJ45 10M / 100M  |
|                    | Serial interface         | 1 RS-485   |
|                    | USB                      | 2xUSB 2.)  |
|                    | Alarm input              | 4  |
|                    | Alarm output             | 1  |
| General            | Input voltage            | 12V (DC)   |
|                    | Consumption              | ≤10W   |
|                    | Operating Temperature    | -10°C...+55°C  |
|                    | Operating Humidity       | 10...90%   |
|                    | Box                      | 1U   |
|                    | Dimension (W x D x H)    | 315×230×45 mm  |
|                    | Weight (With hard disks) | ≤2 kg  |