

## 8-Channel Triplex DVR with 1TB HDD incl.

LTV-DVR-0831-HV



- 8-channel triplex DVR
- 4 audio inputs
- H.264
- resolution and recording speed:  
main stream - CIF, 2CIF: 25 fps, 4CIF/960H 12 fps  
second stream: CIF/QCIF: 25 fps/ channel
- 3 monitor outputs (BNC+HDMI+VGA)
- 1TB HDD incl.
- 2 USB
- IR remote
- motion detector
- RS-485
- Ethernet
- 4 alarm inputs
- 1 alarm output
- Power supply 12V (DC).

Video/audio input	Video input	8xBNC (1.0Vp-p, 75Ω) PAL/NTSC
	Audio input	4xRCA (2.0Vp-p, 1kΩ)
	Two-way audio input	1xRCA (2.0Vp-p, 1kΩ)
Video/audio output	BNC output	1xBNC (1.0 Vp-p, 75 Ω)
	BNC resolution	PAL: 704x576; NTSC: 704x480
	HDMI/VGA output	1 HDMI & 1 VGA
	HDMI/VGA resolution	1920×1080P / 60 Hz, 1600×1200 / 60 Hz, 1280×1024 / 60 Hz, 1280×720 / 60 Hz, 1024×768 / 60 Hz
	Loop output	-
	Audio output	1xRCA (2.0Vp-p, 1KΩ)
Recording	Video compression	H.264
	Audio compression	G.711
	Stream type	Video / Video end audio
	Frame rate	WD1: 12 fps; 4CIF: 12 fps; 2CIF: 25 fps; CIF: 25 fps
	Video bit rate	32...3072Kbps / or user defined, max 3072 Kbps
	Audio bit rate	64 Kbps
	Dual stream	Support; Sub-stream: CIF ,QCIF 25 fps
	Synchronous playback	8 ch
HDD	SATA	1xSATA
	Capacity	Up to 4TB capacity
Interface	Network	1xRJ45 10M / 100M
	Serial interface	1 RS-485
	USB	2xUSB 2.0
	Alarm input	4
	Alarm output	1
General	Input voltage	12V (DC)
	Consumption	≤10W
	Operating Temperature	-10°C...+55°C
	Operating Humidity	10...90%
	Box	1U
	Dimension (W x D x H)	315×230×45 mm
	Weight (With hard disks)	≤4 kg