

HD 720p box camera

LTV-ICDM1-423



- 1/2.5" Progressive Scan CMOS sensor
- Max. HD 720p resolution
- H.264/MJPEG multiple codecs
- True "Day / Night" (mechanical IR cut filter)
- Dual stream
- Bi-directional audio
- Supports ONVIF
- Memory card slot for Micro SD
- Triple power supply: 12V (DC), 24V (AC), PoE

Video	Imaging device	1/2.5" Progressive Scan CMOS
	Effective pixels	2592x1944
	Electronic shutter speed	1/4 - 1/2 000 s
	Resolution	1280x1024
	Max. framerate	Max. 25fps at all resolutions
	Min. illumination	0.7 lux (color) / 0.08 lux (b/w) at F1.2
	Video compression format	H.264 / MJPEG
Lens	Lens mount	C/CS
	Auto iris	DD / AES / Manual
Analog output (Only for installation mode)	Video output	CVBS : 1.0 Vp-p / 75 Ω composite, 704 x 480(N), 704 x 576(P)
	S/N ratio	>50dB (AGC off.)
	Scanning Frequency	PAL: 15.625 kHz x 50 Hz, NTSC: 15.734 kHz x 59.94 Hz
Audio	Audio I/O	Line in / line out (use with external amplifier)
	Audio Compression Format	G.711
Operational	Day & Night	True Day/Night (IR-Cut filter)
	Backlight Compensation	BLC
	Gain Control	AGC
	White Balance	AWB / Manual
	Electronic Shutter Speed	Sens-up (x2)
	Motion detection	4 programmable zones, 10 levels of sensitivity
	Memory Slot	Micro SD. Compatible with SanDisk, Transcend, Kingston, Toshiba: 1Gb, 2Gb, 4Gb, 8Gb, 16Gb
Network	Ethernet	10BASE-T, 100BASE-TX, RJ45
	Protocol	IPv4/6, HTTP, HTTPS, SMTP, UPnP, DNS, Dynamic DNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP
	Web Viewer	Internet Explorer 7.0 or later, Firefox, Chrome, PDA/Smartphones
	Security	HTTPS, login authentication, IP address filtering
	Input Voltage, Current, Power Consumption	12B (DC) 430mA, Max. 5.1W; 24B (AC) 350mA, Max. 5.1W; PoE (IEEE 802.3af) 87.3mA, Max. 4.2W
Miscellaneous	Operating conditions	Indoor
	Operating Temperature	-10° ... +50°C
	Dimensions (WxHxD)	63.6x60.3x81.2 mm
	Weight	0.25 kg