

### HD 720p (1,3Mpix) IR dome camera

LTV-ICDM1-E8231L-V3-10,5



- HD 720p
- Day & Night(ICR)
- Varifocal lens, f=3-10,5 mm
- IR LED, max. 30 m
- H.264
- 12V (DC) / PoE
- IP66, Vandal-Resistant



Video	Imaging Device	1/3" CMOS
	Effective Pixels (H/V)	1280x960
	Electronic shutter speed	1/25 ... 1/100000 c
	Resolution	1280x960
	Max. framerate	Max. 25fps at all resolutions
	Min. illumination	0 lk(IR illumination on)
	Video compression format	H.264
Lens	Mount Type	Build-in, varifocal
	Focal Length	3-10,5 mm
	Iris control	DC
Video output (for installation)	Video output	CVBS : 1.0 Vp-p / 75 Ω composite, 704 x 480(N), 704 x 576(P)
	Scanning Frequency	PAL: 15.625 kHz x 50 Hz, NTSC: 15.734 kHz x 59.94 Hz
Audio	Audio I/O	Line in/ Line out
	Audio Compression Format	G.711A
Operational	Day & Night	Auto (ICR), Color & B/W
	IR LED	Max.30 m
	Backlight Compensation	BLC
	Gain Control	AGC
	White Balance	AWB / Manual (presets)
	Sens-up	-
	Motion detection	Yes
	Alarm I/O	Input 1 / Output 1
	Memory Slot	TF, max. 64GB
Network	Ethernet	RJ45
	Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
	Web Viewer	Internet Explorer
	Security	HTTPS, login authentication, IP address filtering
Mechanical & Electrical & Environmental	Input Voltage-Current	12V (DC), 6.48W; PoE (IEEE 802.3af), 6.48W
	Operating conditions	Outdoor IP66
	Operating Temperature	-40° ... +50°C
	Dimensions (WxHxD)	150×114 mm
	Weight	0.9 kg