

ECONOMY LINE

1 Mpix Network IR Dome Camera

LTV-ICDM1-E9235L-F3.6



Main Features:

- ICR auto switch, true Day / Night
- IR Illumination up to 20m
- 3D DNR, digital WDR
- Support smart phone, iPad, remote monitoring
- P2P Support
- PoE



Video	
Image Sensor	1/4" CMOS
Image Size	1280 x 720
Electronic Shutter Speed	1/25 - 1/1000000s
Max. Framerate	1280 x 720 @ 30 fps
Min. Illumination	0 lux (IR LED ON)
Video Compression	H.264, Motion JPEG
Encode Mode	VBR / CBR
Resolution	720P (1280 x 720), D1, CIF, 480 x 240
Multi-stream	1280 x 720 (1 ~ 30 fps) 1280 x 720 (1 ~ 10 fps) / D1 (1 ~ 30 fps) / CIF (1 ~ 30 fps) / 480 x 240 (1 ~ 30 fps)
Digital DNR	3D DNR
Lens	
(Required) Lens	3.6mm
Lens Mount	M12
Function	
Remote Monitoring	IE browsing, CMS remote control
Day & Night	IR cut filter removable (ICR)
PoE	Yes
WDR	Enhanced Digital WDR
Onvif	Yes
Motion Detection	Yes
Water-proof	IP66
IR-Lights	10 ~ 20m
Network	
Network	1 x RJ45
Protocols	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Miscellaneous	
Power Supply	12V DC, PoE
Power Consumption	< 2W
IR Consumption ON	< 4.5W
Operating Conditions	-20°C ... +50°C, 10% ~ 90% humidity
Dimensions	87 x 108mm
Weight	325g