

Full HD 1080p (2Mpix) IR bullet camera

LTV-ICDM2-623L-F4



- 1/2.8" Progressive Scan CMOS sensor
- Max HD 1080p resolution
- True "Day / Night" (IR cut filter)
- H.264 / MJPEG Network Camera
- Dual Stream
- Motion Triggered Alarm
- ONVIF Compliant
- PoE

Video	Imaging device	1/2.8" Sony IMX-036 CMOS Sensor
	Effective pixels	1984x1225
	Electronic shutter speed	1/4 - 1/2 000 s
	Resolution	1920x1080
	Max. Framerate	Max. 25fps at all resolutions
	Min. illumination	Color: 0.63 lux(F3.5, 50IRE) B/W: 0 lux(IR LED ON)
	Video compression format	H.264 / MJPEG
	S/N Ratio	>50dB (AGC off.)
Lens	Lens type	Fixed Lens
	Focal length	f=4 mm
	Auto iris	Fixed Iris
Analog output (Only for installation mode)	Video output	CVBS : 1.0 Vp-p / 75 Ω composite, 704 x 480(N), 704 x 576(P)
	Scanning Frequency	PAL: 15.625 kHz x 50 Hz, NTSC: 15.734 kHz x 59.94 Hz
Audio	Audio I/O	-
	Audio Compression Format	-
Operational	Day & Night	True Day/Night (IR-Cut filter)
	IR-Light	Built-in, up to 10m
	Backlight Compensation	BLC
	Gain Control	AGC
	White Balance	ATW / Manual
	Electronic Shutter Speed	Sens-up (x2)
	Motion detection	4 programmable zones, 10 levels of sensitivity
	Alarm I/O	-
	Memory Slot	-
Network	Ethernet	10BASE-T, 100BASE-TX, RJ45
	Protocol	IPv4/6, HTTP, SMTP, UPnP, DNS, Dynamic DNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP
	Web Viewer	Internet Explorer 7.0 or later, Firefox, Chrome, PDA/Smartphones
	Security	HTTPS, login authentication, IP address filtering
Miscellaneous	Input Voltage, Current, Power Consumption	PoE (IEEE 802.3af) 140mA, max. 6.7W
	Operating conditions	Indoor
	Operating Temperature	-10° ... +50°C
	Dimensions (WxHxD)	57,9 x 85 mm
	Weight	0,28 kg