

## Full HD 1080p (2Mpix) indoor flat dome camera

LTV-ICDM2-723L-F4



- 1/2.8" Progressive Scan CMOS
- Supports Full HD 1080p resolution
- The "Day / Night" (mechanical IR cut filter)
- Lens with a fixed focal length, f = 4 mm
- IR illumination up to 8 m
- Support codecs H.264, MJPEG
- ONVIF support
- Power supply: PoE

Video	Imaging device	1/2.8" Sony Progressive Scan CMOS
	Effective pixels	2096x1561
	Electronic Shutter speed	1/4 - 1/2 000 c
	Resolution	1920x1080
	Max. framerate	Max. 25fps at all resolutions
	Min. illumination	0.63 lux (color) at F3.5 / 0 Lux (B / W) with IR illumination
	Video compression format	H.264 / MJPEG
	S/N Ratio	>48.8dB (AGC off.)
Lens	Lens type	Fixed lens
	Focal length	f=4 mm
	Iris Control	-
Analog output (Only for installation mode)	Monitor output	Composite output connector: BNC, 75 Ohm 1V pp
	Scanning Frequency	PAL: 15.625 kHz x 50 Hz NTSC: 15.734 kHz x 59.94 Hz
Audio	Audio I/O	-
	Audio compression format	-
Operational	Day / Night	Yes (Mechanical IR Cut filter)
	IR-light	Built-in, up to 8 m
	Blacklight compensation	BLC
	Gain Control	AGC
	White balance	AWB / manual (preset)
	Electronic shutter speed	Sens-up (x2)
	Motion detection	4 programmable zones, 10 levels of sensitivity
	Alarm I/O	-
Network	Memory Slot	-
	Ethernet	10BASE-T, 100BASE-TX, RJ45
	Protocol	IPv4/6, HTTP, HTTPS, SMTP, UPnP, DNS, Dynamic DNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP
	Web viewer	Internet Explorer 7.0 or higher, Firefox, Chrome, PDA / Smartphone
Security	HTTPS, login authentication, IP address filtering	
Miscellaneous	Input Voltage, Current, Power Consumption	PoE (IEEE 802.3af) 100mA max. 4.8V
	Operating conditions	Indoor
	Operating temperature	-10°C...+45°C
	Dimensions (WxH)	130x76 mm
	Weight	0.26 kg