

## HD 720p (1,3Mpix) IR bullet camera

LTV-ICDM2-E6231L-F4



- 1/2.9" Progressive Scan CMOS
- Full HD 1080p
- Day & Night(ICR)
- Fixed lens, f=4 mm
- IR LED, 20-30 m
- H.264
- ONVIF
- 12V (DC) / PoE
- Weatherproof to IP66, -40°C...+50°C

Video	Imaging Device	1/2.9" CMOS
	Effective Pixels (H/V)	1920x1080
	Electronic shutter speed	1/25...1/100000 c
	Resolution	1920x1080
	Max. framerate	Max. 25fps at all resolutions
	Min. illumination	0 lK(IR illumination on)
	Video compression format	H.264
Lens	Mount Type	Fixed lens
	Focal Length	4mm
	Iris control	-
Video output (for installation)	Video output	CVBS : 1.0 Vp-p / 75 Ω composite, 704 x 480(N), 704 x 576(P)
	Scanning Frequency	PAL: 15.625 kHz x 50 Hz, NTSC: 15.734 kHz x 59.94 Hz
Audio	Audio I/O	Line in
	Audio Compression Format	G.711A
Operational	Day & Night	Auto (ICR), Color & B/W.
	IR LED	20 – 30 m
	Backlight Compensation	BLC
	Gain Control	AGC
	White Balance	AWB / Manual (presets)
	Sens-up	-
	Motion detection	Yes
	Alarm I/O	-
Memory Slot	-	
Network	Ethernet	RJ45
	Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
	Web Viewer	Internet Explorer
	Security	HTTPS, login authentication, IP address filtering
Mechanical & Electrical & Environmental	Input Voltage-Current	12V (DC), 5W;PoE (IEEE 802.3af), 5W
	Operating conditions	Outdoor IP66
	Operating Temperature	-40°...+50°C
	Dimensions (WxHxD)	87×219 mm
	Weight	0.6 kg