

IP CAMERAS ECONOMY LINE

Full HD 1080p (2Mpix)

IR outdoor dome camera

LTV-ICDM2-E8231L-F4



- Full HD 1080p (1920×1080)
- Day & Night(ICR)
- Fixed lens, f=4 mm
- IR LED, max. 20 m
- H.264
- 12V (DC) / PoE
- IP66, Vandal-Resistant



Video	Imaging Device	1/2.9" CMOS
	Effective Pixels (H/V)	1920×1080
	Electronic shutter speed	1/25 . . . 1/100000 c
	Resolution	1920×1080
	Max. framerate	Max. 25fps at all resolutions
	Min. illumination	0 lk(IR illumination on)
	Lens	Video compression format
Mount Type		Build-in, with fixed focal length M12
Focal Length		4 mm
Video output (for installation)	Iris control	-
	Video output	-
	Scanning Frequency	PAL: 15.625 kHz x 50 Hz, NTSC: 15.734 kHz x 59.94 Hz
Audio	Audio I/O	Line in
	Audio Compression Format	G.711A
Operational	Day & Night	Auto (ICR), Color & B/W.
	IR LED	Max. 20 m
	Backlight Compensation	BLC
	Gain Control	-
	White Balance	AWB / Manual (presets)
	Sens-up	-
	Motion detection	Yes
	Alarm I/O	-
Network	Memory Slot	-
	Ethernet	RJ45
	Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
	Web Viewer	Internet Explorer
	Security	HTTPS, login authentication, IP address filtering
Mechanical & Electrical & Environmental	Input Voltage-Current	12V (DC), 5W; PoE (IEEE 802.3af), 5W
	Operating conditions	Outdoor IP66
	Operating Temperature	-40° . . . +50°C
	Dimensions (LxD)	116×91 mm
	Weight	0.6 kg