

Full HD 1080p (2Mpix) Box Camera

LTV-IDCM2-E8231L-F4



- 1/2.9" Progressive Scan CMOS
- Full HD 1080p (1920×1080)
- Day & Night(ICR)
- Fixed lens, f=4 mm
- IR LED, max. 20 m
- H.264
- 12V (DC) / PoE
- Vandal-Resistant
- Weatherproof to IP66, -40°C...+50°C

| | | |
|---|--------------------------|--|
| Video | Imaging Device | 1/2.9" CMOS |
| | Effective Pixels (H/V) | 1920×1080 |
| | Electronic shutter speed | 1/25...1/100000 c |
| | Resolution | 1920×1080 |
| | Max. framerate | Max. 25fps at all resolutions |
| | Min. illumination | 0 lK(IR illumination on) |
| | Video compression format | H.264 |
| Lens | Mount Type | Build-in, with fixed focal length M12 |
| | Focal Length | 4 mm |
| | Iris control | - |
| Video output (for installation) | Video output | - |
| | Scanning Frequency | PAL: 15.625 kHz x 50 Hz, NTSC: 15.734 kHz x 59.94 Hz |
| Audio | Audio I/O | Line in |
| | Audio Compression Format | G.711A |
| Operational | Day & Night | Auto (ICR), Color & B/W. |
| | IR LED | Max. 20 m |
| | Backlight Compensation | BLC |
| | Gain Control | - |
| | White Balance | AWB / Manual (presets) |
| | Sens-up | - |
| | Motion detection | Yes |
| | Alarm I/O | - |
| | Memory Slot | - |
| Network | Ethernet | RJ45 |
| | Protocol | TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP |
| | Web Viewer | Internet Explorer |
| | Security | HTTPS, login authentication, IP address filtering |
| Mechanical & Electrical & Environmental | Input Voltage-Current | 12V (DC), 5W; PoE (IEEE 802.3af), 5W |
| | Operating conditions | Outdoor IP66 |
| | Operating Temperature | -40°...+50°C |
| | Dimensions (LxD) | 116×91 mm |
| | Weight | 0.6 kg |