

## Portable Multi-Function AHD/TVI TESTER

LTV-MCL-07-TM



### Main Features:

- 7" LED Display
- Input Resolution up to 1080p
- Power supply of 12V DC cameras via integrated battery possible
- PTZ control
- HDMI/VGA input
- Supports FHDA/ AHD /TVI/CVBS



Display		
Resolution	7" 1024 (H) x (R.G.B) x 600 (V)	
Visible area	153.6 (W) x 90.0 (H) mm	
Dot Pitch	0.5 (W) x 0.15 (H) mm	
Brightness	500 cd/m <sup>2</sup>	
Contrast	700:1	
Reaction Time	10 ms	
Video		
Input	AHD	720P/1080P
	FHDA/TVI	720P/1080P
	HDMI	720p/1080i/1080p
	VGA	VGA (640x480) ~ UXGA (1600x1200)
	CVBS	NTSC/PAL 1.0Vp-p
Output	CVBS	THRU Output + Pattern Indication
Power Supply		
Input	DC 12V	
Output	DC 12V (1A)	
PTZ Control		
RS-485	PELCO-D, PELCO-P, Yaan, Samsung, Lilin, Molyax, Minking, AD, Fastrax, CBC, SONY, LG, DTA, Pearmain, Vicon, Vcltp, DHYCT06, SANYO	
Miscellaneous		
Accumulator	Li-Polymer: 7.4V, 5200mAh	
Operating Temperature	0°C ... +50°C, 0% ... 80% Humidity	
Dimension	250 (W) x 158 (H) x 50 (D) mm	