

FULL HD ANALOG

16 Channel Full HD Analog Tribrid DVR with 2TB HDD

LTV RTE-160 02

Article-No.: 37000009



Main Features:

- Supports Analog, Full HD Analog and LTV Eco-Line IP Cameras (up to 3 Mpix)
- H.264 video compression
- 1920 × 1080 resolution
- HDMI and VGA output
- 8 channel simultaneously playback



Video/Audio		
Compression	H.264 High profile	
Video Input	BNC x 16	
Video Output	VGA x 1: 1080P, HDMI x 1: 1080P	
Audio Input	RCA x 16	
Audio Output	RCA x 1	
2-Way Audio	1 channel	
Recording		
Resolution	1080P (1920 x 1080), 720P (1280 x 720), WD1, D1	
Frame Rate (fps)	1080P	200fps (PAL) / 240fps (NTSC)
	720P/WD1/D1	400fps (PAL) / 480fps (NTSC)
	Supports 8CHIP 1080P@30fps real time recording	
Bitrate	1 M ~ 4 Mbps VBR/CBR	
Quality	6 levels	
Mode	Manual, timer, motion, sensor	
Playback		
Playback	8	
Search	Time/calendar search, event (motion, external alarm)	
Functions	Play, pause, FF, FB, digital zoom	
Alarm		
Mode	Sensor, motion, video loss	
Triggering	Record, PTZ move, alarm out, e-mail, etc.	
Network		
Interface	RJ 45 10M/100M/1000M	
IP Channels	8/24Mbps	
IP Resolution	3MP/1080P/960P/720P/WD1/D1	
IP Frame Rate	3MP:100fps(PAL)/120fps(NTSC) 1080P/960P/720P: 200fps(PAL) / 240fps(NTSC)	
Dual-stream	Encode recording stream and network stream respectively	
Protocols	TCP/IP, UDP, DHCP, DNS, PPPoE, DDNS	
Smartphone	iPhone, Android	
Interface		
HDD	SATA x8 (7 unused)	
RS485	RS485 x 2 (one for PTZ, another for keyboard)	
USB	USB 2.0 x 2 (for mouse and USB backup device)	
Miscellaneous		
Dimensions	430 x 450 x 89 mm (WxDxH)	
Delivery Content	Remote control, mouse	
Power Supply Voltage	12V DC / ATX	
Power Supply	< 26W (without HDD)	
Operating Temperature	10°C...+50°C, 10% ... 90% humidity	