

## 16 Port Managed PoE Switch

LTV-S7216E-POE

Article No.: 45000003



### Main Features:

- LWL uplink port
- uplink port: 150 m
- operating temperature: 0°C ... +55°C
- sheet metal



Power	
Voltage Range	100-240V AC
Consumption	320W
Network Connector	
Network Port	1-16 ports: 10/100 Mbps Ethernet port, adaptive control
	2x uplink port: 10/100/1000 Mbps Ethernet port
	2x SFP: SFP optical fiber module, 1000 Mbps
Transmission Distance	1-16 ports: recommended 120m, max. 150m
	Uplink port: max. 150m
	SFP: depend on the optical module performance
PoE Protocol	IEEE802.3af/at
PoE Power Supply	End span
PoE Power Consumption	Each port <30W, total <250W
Network Standard	IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX, IEEE802.3ab 1000BASE-T, IEEE802.3z 1000BASE-SX/LX
Switch Capacity	16G
Management	
Management	L2
Protection	
Communication Port Lighting Protection	Level 3, Pro:IEC61000-4-5
ESD	Level 3, Pro: IEC61000-4-2
Mechanical	
Dimensions (L x W x H)	442 x 263 x 44,5 mm
Working Environment	0°C...+55°C, humidity (non-condensing) 0-95%
Material	Sheet metal
Color	Black
Weight	3,54 kg