

24 Port Full Gigabit PoE Managed Ethernet Switch

LTV-S7224E-POE

Article No.: 45000004



Main Features:

- 24 x 10/100/1000 BASE-T Ethernet ports (PoE)
- 2 x 10/100/1000 BASE-T Ethernet Uplink ports
- web-based management; VLAN, QoS, RSTP, SNMP etc.
- High-speed data transfer, large-stream video and data transmission in security surveillance
- operating temperature: -10°C ... +50°C



Power	
Voltage Range	100-240V AC
Consumption	450W
Network Connector	
Network Port	1-24 ports: 10/100/1000 Base-T Ethernet ports (PoE)
	2x 10/100/1000 Base-T Ethernet ports
	2x 1000 Base-X SFP
Transmission Distance	Ethernet ports: 100m
	SFP: depend on the optical module performance
PoE Protocol	IEEE802.3af/at
PoE Power Supply	End span (1/2(+), 3/6(-))
PoE Power Consumption	Each port <30W, total <390W
Network Standard	IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3 IEEE802.3x, IEEE802.3z, IEEE802.3ae, IEEE802.1Q, IEEE802.1p, IEEE802.3ad, IEEE802.1D, IEEE802.1X
Switch Capacity	56 Gbps
Management	
Management	L2+PoE
Protection	
Communication Port Lighting Protection	6KV, Per: IEC61000-4-5
ESD	6KV/8KV, Per: IEC61000-4-2
Mechanical	
Dimensions (L x W x H)	442 x 305 x 44.5 mm
Working Environment	-10°C...+50°C, humidity (non-condensing) 5-95%
Material	Sheet metal
Color	Black
Weight	4.35 kg