

ANALOG FULL HD

20x IR HD High Speed Dome Camera

LTV-TSDNO20LH-M2




Main Features:

- 1/3" CMOS progressive scan-sensor, 20x optical zoom
- Full HD Analog video output: 1920 x 1080P@25/30fps
- 80m IR Lights
- Pan/Tilt preset speed up to 240°/s
- Video Output: 1 CH Full HD Analog
- IP66 ingress protection
- Windscreen wiper
- Heater



Dimension:



Video	
Image Sensor	1/3" Progressive CMOS
Image Size	1920 (H) x 1080 (V) 2Mpix
Horizontal Resolution	1000 TVL
Min. Illumination	0 lux
S/R Ratio	>50dB
Video Compression	H.264
Focus Mode	Auto/Manual
Lens	
Focal Length	20x Zoom, f=4.7~94mm, F1.6~F3.5
PTZ	
Pan Range	360° continuous rotation
Pan Speed	Preset Speed: 240°/s, Manual Speed: 0.5~90°/s
Tilt Range	0~90° (auto flip)
Tilt Speed	Preset Speed: 240°/s, Manual Speed: 0.5~90°/s
Function	
Prest Position	255
Patrol	8
Trace	4
Time Task	8
Scan	2
Park Position	YES
Auto Flip	YES
Alarm Input	7
Alarm Output	1
Alarm Linkage	YES
Wiper	YES
Video Output	Full HD Analog: 1.0Vp-p, 75 Ω, PAL/NTSC CVBS: 1.0Vp-p, 75 Ω, PAL/NTSC
IR	
Alarm	7
Analog Output	CVBS
IR LED	10PCS 42mils Array LED
Distance	120m
Miscellaneous	
Power Supply	24V AC/3000mA
Consumption	15W (max. 65W, heater + IR Lights on)
Waterproof	IP66
Weight	5 kg
Dimension Ø	Ø 216 x 349 mm
Working Environments	-40°C ... +60°C, <95% humidity