

Barlock™ 200 series



Readers and Keypads



Barlock™ Readers/Keypads

The Barlock™ reader family consists of swipe or insert BarCode™ readers which utilize a covert bar-code. The readers may be combined with keypads for higher security applications. All readers offer a clear indication of card status through the use of green and red LEDs.

All Barlock readers are designed to interface effortlessly with Barlock processors. The readers can read proprietary facility bar code symbology. They can also adapt to standard bar code symbologies which allows them to adapt to existing systems, thereby saving money. Plus, Barlock allows for easy, in-house badge production.

Barlock keypads may be used in simple code only applications or can provide additional security in card and PIN operation mode.

Features

- Control Building Access
- LED Status Lights
- Reads Proprietary Facility Bar Code Symbology
- Covert Barcode to Prevent Duplication
- Surface Mount Design Available
- Easy Interface with Barlock™ Processor Series
- Easy In-House Low-Cost Badge Production
- UL Listed ALVY. BP6777

Options

- Surface mount design is available and eliminates the need for a cut-in back box.

Companion Products

- Barlock™ Processors
- Remote Access Memory Module (RAMM)
- AXxess™ 202/NS — Security Management System

Specifications

General

READERS AND KEYPAD FEATURES

- Accepts standard badges, membership cards or other related documents with a thickness of up to 1/8" (3.2mm)
- Card status indicated by red and green lights on the front of the readhead
- Swipe reader allows various BarCode™ placement positions
- Numeric membrane keypad
- Easy in-house badge production

Reader Models

SURFACE MOUNT SWIPE READER (MODEL-116)

- Fully self-contained reader package
- Mounts directly to Wall surface (no back box required):
3.38"H x 2.28"W x 1.535"D
(8.5cm x 6cm x 3.89cm)
- Read channel 3/4" (1.9cm) above mounting surface

STANDARD ELECTRICAL BOX SWIPE READER (MODEL-117)

- Designed for installation in a standard electrical back box: 2" x 3" x 3.5" (5cm x 7.6cm x 9cm)
- Front plate: 4.5"H x 2.75"W (11.4cm x 6.99cm)

STANDARD ELECTRICAL BOX INSERT READER (MODEL-159)

- Designed for installation in a standard electrical back box: 2" x 3" x 3.5" (5cm x 7.6cm x 9cm)
- Front plate: 4.5"H x 2.75"W (11.4cm x 6.99cm)

www.maxxess-systems.com

MAXxess Systems Headquarters

1515 S. Manchester Ave.

Anaheim, CA USA

92802-2907

Tel 714.772.1000

800.842.0221

Fax 714.780.7592

Email sales@maxxess-systems.com

Service & Technical Support

Tel 714.772.1000

800.842.0221

Fax 714.780.7592

Email support@maxxess-systems.com

MAXxess Systems Europe Ltd.

Beaumont

The Conference Centre

Burfield Road

Old Windsor, Berkshire

England, SL4 2JP

Tel +44 (0) 1753 721075

Fax +44 (0) 1753 721076

Email sales@maxxess-systems.com

Service & Technical Support

Tel +44 (0) 1753 721075

Fax +44 (0) 1753 721076

Email support@maxxess-systems.com

Information furnished by MAXxess is believed to be accurate and reliable. However, no responsibility is assumed by MAXxess for its use nor for any infringements of patents or other rights of third parties that may result from its use. No license is granted by implication or otherwise under any patent rights of MAXxess Systems, Inc. Specifications subject to change without notice.