

# TS400

# TS410

Actual size 205 x 205 x 64mm



TS400

Actual sizes Keypad 130 x 130 x 30mm  
Control panel 242 x 237 x 86mm



TS410

The TS400 and TS410  
are six zone intruder  
alarm control panels  
developed specifically  
for domestic and small  
commercial premises.

- Final exit zone plus five programmable zones, capable of monitoring fire, personal attack, intruder and an optional Keyswitch which can be used to set and unset your alarm system.
- Simple three button setting allowing you to full set and part set the system (Part set is quiet, to avoid waking other members of the household).
- Option to connect up to four remote keypads, allowing control from different areas of the premises.
- The system can be enhanced by connecting the SD1+ Speech Dialler which uses the telephone line to inform third parties of an alarm condition.
- The system allows two different user passcodes to operate the system.
- The TS400 incorporates an integral keypad and display, whilst the TS410 is housed in a metal cabinet which is mounted discreetly within the premises, and the system is operated from a remote keypad.

## Product Features

Model	TS400	TS410	TSD402
Zones	6	6	6
Number of remote Keypads	4	4	4
Display Type	LED	LED	LCD/LED
Event Log	4	4	64
User Codes	2	2	2
Integral Speech Dialler	No	No	Yes



# TSD402



Actual size 205 x 205 x 64mm



Actual sizes 130 x 130 x 30mm

The TSD402 is a six zone intruder alarm control panel incorporating speech dialling technology developed specifically for domestic and small commercial premises.

- The TSD402 offers all the features of the TS400 and includes an integral Speech Dialler and 16 character LCD display.
- The integral Speech Dialler connects to the telephone line and informs third parties of an alarm condition, whilst the LCD display provides clear on-screen instructions to aid setting and unsetting.
- Option to connect up to four remote keypads, allowing control from different areas of the premises.
- Up to 60 seconds message recording time.
- Call Acknowledgement facility.
- Integral microphone and loudspeaker.
- When activated, the alarm system dials any combination of the three chosen telephone numbers.
- It will send one of three messages warning of various situations such as fire, burglary or personal attack.
- The messages can be re-recorded as often as required.
- The system is approved for use on the telephone network by the British Approvals Board of Telecommunications (BABT).

Product Features table on reverse

dealer details

