



Specification

Item	NVS121A
Remote management	Configuration and system log can be accessed via web browser and Ftp application remotely
Networking	
Protocol	TCP,UDP,IP,HTTP,DHCP,PPPoE,RTP,RTSP
Ethernet	Ethernet (10/100Base-T),RJ-45 connector
Video	
Compression	MPEG4 SP
Video input	1 BNC composite video input with NTSC / PAL auto sensing
Analog output (loop-through)	1 Vp-p composite output 75ohm.
Image size	Full D1 (720X480 in NTSC,720X576 in PAL)
	CIF (350X240 in NTSC,352X288 in PAL)
	QCIF (160X112 in NTSC,176X144 in PAL)
Image quality	CIF/ Full D1/ QCIF
Others	Watch dog timer 5 sec.
	2 DI/ 2 DO event triggered via Ethernet
	Layer 2, 3
Audio	Yes
Frame rate	30fps at 720X480 - NTSC
	25fps at 720X576 - PAL
RS485	1 x RJ-45
Viewing system requirement	
Protocol	Standard internet TCP/IP
Operating system	Win 2000, Win XP
Browser	Internet Explorer 6.0 or above
Security	User authorization needed for protecting camera access
Pan/tilt/zoom control	Automatic PTZ camera detection with Pelco-D protocol
	Clear data command driver is supported
LED indicator	Hearbeat, status, network
General	
Power input	DC12V
Operating temperature	0°C ~ 50°C (40 ~122°F)
Operating humidity	10% ~ 90%
Dimensions (W x H x D)	112 x 37.2 x 119 mm
Weight	350g (0.6 lb.)