



# SDM126 Indoor Mini Dome Camera

600TVL, F2.0, f:2.8 mm, Digital Day/Night, DC12V



## Specification

Signal System	NTSC	PAL
<b>Image System</b>		
Image Area	4.9mm x 3.7mm	
Image Sensor	Sony 1/3" Super HAD CCD II	
Effective Pixel (H x V)	768 x 494	752 x 582
<b>Electronic</b>		
Scanning System	2:1 Interlace V: 59.94Hz, H: 15.734KHz	2:1 Interlace V: 50Hz, H: 15.625KHz
Sync System	Internal	
Horizontal Resolution	600 TVLines	
Built-in Lens	F2.0, f=2.8mm	
View Angle	f=2.8mm Horizontal:90°/ Vertical: 80°	
Gamma Correction	0.45	
Min. Illumination	0.2 Lux (F2.0@30IRE)	
S/N Ratio	More than 50dB (AGC off)	
White Balance	Auto	
Electronic Shutter	1/60 ~ 1/100,000 Sec.	1/50 ~ 1/100,000 Sec.
BLC	Off	
Day/Night Mode	Auto	
Gain Control	Auto	
Video Output	1Vpp composite output 75 ohm	
<b>Power supply</b>		
Power Requirement	DC12V ± 10%	
Power Consumption	1.5 W(max)	
<b>Environment</b>		
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)	
Operating Humidity	90% RH	
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)	
<b>Mechanism</b>		
Dimensions (D X H)	Ø107mm x 64 mm	
Weight (g)	300 g	
	SDM126-HN1-28 (White, 2.8mm)	SDM126-HP1-28 (White, 2.8mm)