

Linux based 8-ch digital video recorder













Items	Description	
System		
OS	Embedded Linux	
Video Inputs	4/8	
Video Outputs	D type 15 Pins VGA and External TV-Out (Optional)	
Audio	1 channel audio input and 1 channel output	
Video Format	NTSC/PAL	
Multi-Tasking	Yes	
Display		
User Interface	800*600, very user friendly	
Frame rate	Realtime display	
Resolution	640*480	
HDD Usage Display	Yes	
Motion to Zoom	Yes	
Hidden Camera	Yes	
Video Loss Detection	Yes	
Image Parameter Adjustment	Brightness/Contrast/Hue/Saturation for each camera	
Recording		
Compression	MPEG-4 like Compression	
Resolution	640*480,640*240,320*240	
Frame rate	NTSC: 120, PAL: 100@320*240(4CH); NTSC:240, PAL:200@320*240(8 Ch)	
Pre-Schedule Recording	By 7days x 24hours, set each hour as: recording by motion, continuously recording, non-recording	
Motion detection area	Define any 8x8 cell for motion detection. Free combinations of detected areas. No limitation on the number of detection areas.	
Motion detection sensitivity	10 ranges per camera	
Pre-Recording	0~10 sec	
Post-Recording	0~20 sec	
Watermark	Yes	
Date Code	Recording includes time/date information. To prevent date code from being modified	
Playback		
Playback channels	4 channels playback at the same time	
Playback mode	Play, Pause, frame by frame play, fast forward, fast backward	
Search	By Calendar, and time bar (hour/minute)	
Video Enhancement	De-interlace, Sharpen	
Image Adjustment	Brightness/Contrast	

^{*} Specifications subject to change without notice





Linux based 8-ch digital video recorder













Items	Description
Remote	
Network Access	LAN/ WAN/ Internet, by Ethernet/ Modem
Network Interface	10/100/1000 Ethernet
Remote Monitoring	JPEG mode or MPEG4 streaming.
Remote Playback	Yes. with MPEG4 Streaming Technology.
Remote Setup	Yes
Download and Local Play	Yes
Central Management	Yes
Remote Backup	by Windows Network Neighborhood
DHCP Support	Yes
DDNS Support	Yes
i-Mode	Yes
Alarm	
Inputs	4 NC/NO dry contact inputs
Outputs	4 NC/NO relay
IO & Camera Relations	1-1, 1-many, many-1, many-many
Alarm to notice	by Email / FTP / SMS (Short Message requires GSM modem)
Storage & Backup	
Hard Disk Storage	2 3.5" internal rack
Large HDD Support	With ATA 133 support HDD 40~400GB
RAID support	Support IDE/SCSI RAID
Backup	USB/ IDE burning device(CD-R/RW, DVD±R/RW); USB storage (Pen Drive, HDD)
HDD SMART Diagnostics	Yes
Other	
Password protection	100 user accounts, each one can see different cameras
PTZ camera support	Yes
Power Down Management	Yes. Auto-recovery when power back
Watchdog	Yes Hardware Watchdog.
Time Zone/Daylight Saving	Yes
AVI Format Export	Yes
Time Sync	Support Time Server, FM and RTC Time Sync
UI Language	8 languages in single software: English, French, German, Japanese, Polish, Portuguese, Spanish, Traditional Chinese
Dimension	
Power	100~230V AC, 50/60Hz
Case Color	Silver
Dimension (DVR)	405W*350D*89H
Weight (net)	6.5 Kg

^{*} Specifications subject to change without notice

