

NEW! GEMINI™ 8 TO 16 ZONE HYBRID CONTROL



GEMINI

P816



P816 Performance Pak featured here.

Now there's an economical hardwire/wireless control panel that works seamlessly with the same Gemini keypads and wireless you've used with the GEM-P1632, P3200 and P9600. Introducing the GEM-P816!

- 8 hybrid zones on-board including two 2-wire fire zones
- With multiplexing, can accommodate up to 16 EOL zones (from alpha keypads or multiplex modules, including the new low-cost GEM-EZM4/8 Expansion Module).
- Up to 16 users
- Supports up to 7 standard Gemini keypads, including the GEM-RP1CAe2, the GEM-RP2ASe2, and the brand-new digital display GEM-RP3DGTL.
- Comes in three convenient packages

GEMINI™
BY NAPCO
The Power of Innovation

NEW! GEMINI™ P816 ZONE HYBRID CONTROL



GEMINI

Uses all three Standard Keypads, too!

1
GEM-RP1CAe2



2
GEM-RP2As2

3
GEM-RP3DGL



Waterproof
GEM-WP PANIC



Seamlessly Supports all Gemini Wireless Transmitters using Standard Receivers (GEM-REC18 or REC16)!

FEATURING:

- 8 Hybrid Zones On-board (hardwire or wireless), including 2 2-wire fire zones
- Up to 16 EOL Zones with Multiplexing (zones from RP1CAe2 alpha keypads or multiplex expansion modules)
- Uses new low-cost GEM-EZM1/8 or 8-zone GEM-EZM1/8 Expansion Modules
- Up to 16 Users
- Supports choice of up to 7 Standard Gemini Keypads (GEM-RP1CAe2 Custom Alpha, GEM-RP2As2 Alpha/icon and new Digital Display GEM-RP3DGL)
- 256 Event Logging
- 3 Outputs
- Interior Bypass Group
- Choice of Gemini™ RF Receivers
- Event Log with Open/Close Suppression
- Supports GEM-EVA Annunciator and Word™ Talking Phone-In Interface Module
- Includes Transformer

SPECIFICATIONS:

- Input Power: 165W/AC via Class 2 Plug-in 20 VA Transformer
- Aux & Remote Power: 12Vdc regulated
- 500 mA standby current rating with 20VA transformer, supplied
- 650 mA standby current rating with optional 40VA trans 650mA
- Alarm Current: 2A
- Loop Resist: 300 ohm max; 50 ohm max for 2-wire fire
- Burg Voltage Output: -1 Programmable Negative Outputs -2
- Operating Temp: 0-49 degrees C
- Communication Formats: Ademco Point ID, Silent Knight, Fast/Slow, Redionics Fast/Slow, Universal High Speed, SA and Pager.

ORDERING INFORMATION:

- GEM-P816 GEM-P816 Control and Transformer.
- GEM-P816 PERFORMANCE PAK GEM-P816 Control, GEM-RP3DGL Digital Keypad and Transformer.
- GEM-P816 PERFORMANCE PAK WP GEM-P816 Control, GEM-RP3DGL Digital Keypad interior siren, jack & cord, 4Ah 12V Battery PIR1710 70°x60° PIR Detector and Transformer.



NAPCO SECURITY GROUP
333 Bayview Avenue,
Arlingville, New York 11701 USA
1-800-645-9445

www.napcosecurity.com