



Features

- ► Supports Auto-Negotiation and Auto MDI/MDI-X
- ► Supports 802.3x Flow Control
- Fan-less design (no noise) for office environment
- ▶ Support Energy Efficient Ethernet IEEE 802.3az
- ► Plug and Play installation








Warranty

▶ 1-Year Warranty

Typical Application



Specifications

-	
Ethernet	
Standards	IEEE802.3 10Base-T
	IEEE802.3u 100Base-TX
	IEEE802.3ab 1000Base-T
	IEEE802.3az Energy Efficient Ethernet
	IEEE802.3x Flow Control
Processing Type	Store-and-Forward
Forward Filter Rate	14,880pps (10Mbps)
	148,800pps (100Mbps)
	1,488,000pps (1000Mbps)
Packet Buffer Memory	1Mbit
Address Table Size	4K MAC Addresses
Connector	8 x RJ45
Electrical and Mechanic	al
Input Power	12VDC, DC Socket
Power Consumption	1A, 12W (Max.)
LED Indicators	
Power	Power Status
Ethernet (Per Port)	LINK, Activity
Dimensions (W x D x H)	158 x 111 x 26 mm
Weight	0.5 Kg
Casing	Metal Case
Mounting options	Desktop



Specifications

Environmental	
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Relative Humidity	10% to 90% non-condensing
MTBF	> 100,000 hrs

Regulatory Approvals

ISO9001

FCC

CE

Ordering Information

Available Model	Description		
EC8200	Econ-line Unmanaged 8-port 10/100/1000Base-T Ethernet Switch		
Package Checklist			
 ■ Unmanaged Network Switch ■ 1.5A 12VDC External Power Adapter with US, UK, EU or AU type on request ■ Quick Installation Guide 		x 1 x 1 x 1	

