

Smart PIN Reader

The PAC Smart PIN Reader is a dual contactless Mifare® card and keypad reader designed specifically for high traffic areas, where medium to high security levels are specified.

The combination of Mifare technology and keypad PIN verification gives increased security by only granting access to secure areas, once the user has successfully entered the correct PIN number into the reader keypad after the Mifare ID has been verified by the access control system. This reduces the risk of lost or stolen cards that haven't been deleted from the access control system being used to gain entry into high security areas.



Key Features:

- Contactless Mifare® technology
- User PIN verification
- 12 button illuminated Keypad
- Fits UK single gang back box for easy installation
- Conventional security wiring
- Interchangeable with any existing PAC readers
- Visual and audible feedback
- IP67 standard finish for internal and external applications
- 2 year warranty

Concealed fixings allow the reader to be mounted directly on to a flush surface single gang UK back box, providing a fast and simple solution to many site requirements.

The PAC Smart PIN Reader is a low profile, robust epoxy filled unit that is built to withstand the harshest of environments and operations. It can be installed in new sites or as an upgraded reader to existing proximity access control systems.

The reader incorporates a red/green LED and buzzer that can be configured within the security system to provide visual and audible feedback for confirmation on access control modes.




Features & Specification

Description	Smart PIN Mifare® Access Reader
ID Technology	Mifare®
Dimensions	H: 90mm W: 90mm D: 27mm
Output Formats	PAC
Weight	140g nominal
Maximum Read Range	Up to 60mm
Environment	IP67 - Indoor / Outdoor weather resistant
Maximum Current Requirements	Normal 120mA Activated 140mA
Cable Distance	0.22mm ² cable 100m max 0.33mm ² cable 250m max
Operating Temperature	-10° to +55° C
Operating Humidity	0 to 90% relative humidity non-condensing
Audiovisual Indication	LED and buzzer
Keypad	12 button illuminated
Material	Charcoal plastic
Certifications	CE Mark, Fifteen EU Countries under the R&TTE Directive (EN60950 - ITE Electrical Safety, ETS EN 300 330 - SRD, and ETS EN 301 489 - EMC)

Ordering Information

40196	PAC Smart PIN Reader
40193	PAC Smart PIN Reader Backbox

Smart Pin Reader



ACCESSORIES

PAC® Smart Card

40090 Smart Cards



- Uses MiFare® (13.56MHz) proximity technology
- Durable & robust
- Offers a unique ID code
- Meets ISO standards for thickness
- Can be used with all direct image or thermal transfer printers
- Design your own card layout using Badge Designer in SecureNet or EasiNet Residential
- H: 54 x W: 86 x D: 0.76mm

Backbox

40193

Backbox for PIN Reader



STANLEY Security Products

PAC Access Control, 1 Park Gate Close, Bredbury, Stockport, Cheshire, SK6 2SZ
Tel: +44 (0) 161 406 3400 Fax: +44 (0) 161 406 8984 Email: customerservices@stanleysecurityproducts.com
www.stanleysecurityproducts.com

Stanley Security Products is a sales channel of Stanley Security Solutions
Stanley Security Solutions Ltd. Registered in England and Wales No. 181585. Registered Office: Stanley House, Bramble Road, Swindon, Wiltshire SN2 8ER. VAT No. 232 2446 95
All reasonable care has been taken to ensure that the information contained in this publication is accurate as at the date of printing. Such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing in the products, services or statements referred to in this publication.