

WV-NP1000

Network Static Cameras

1 Megapixel resolution

Dual MPEG4 and JPEG digital signal output

Built in network interface

Auto Back Focus

Built in SD memory card slot for FTP backup



1 Mega-Pixel Colour Network Camera

null

General

Type	Mega Pixel Network Camera
Pick-up Device	1/3-type interline transfer CCD

Effective Pixels

Horizontal	1296.0
Vertical	966.0

Scanning Area [mm]

Horizontal	4.8
Vertical	3.6
Signal	PAL
Synchronization	Internal (INT), Multiplexed Vertical Drive (VD2)
Scanning Mode	Full Scanning Mode: 12.5 fps progressive scan, Partial Scanning Mode: 25 fps 2:1 interlace scan

Scanning Frequency

Horizontal [KHz]	15.625
Vertical [Hz]	50.0

Resolution

Horizontal	600 TV lines (Colour), 780 TV lines (B/W)
------------	---

Vertical	-
Dynamic Range	-
Signal-to-Noise Ratio	50 dB minimum (AGC: OFF)
Minimum Illumination (Colour)	1.0 lux
Minimum Illumination (B/W)	0.06 lux
Weather Protection	-

Power Source

Voltage AC [V]	220-240
Voltage DC [V]	0.0
Frequency [Hz]	50.0
Power Consumption [W]	10.5
PoE (Power over Ethernet)	-

Ambient Operating Temperature [degrees C]

Minimum	-10.0
Maximum	50.0

Ambient Operating Humidity [%]

Minimum	0.0
Maximum	90.0

Dimensions [mm]

Width	84.0
Height	83.0
Depth	197.5
Weight [kg]	0.97

Main Functions

Controller Interface	Coaxial multiplex/Ethernet
Control Functions	-
Auto Gain Control (AGC)	ON (LOW), ON (MID), ON (HIGH), OFF
Zoom Speed	-
Focus Speed	-
Iris / Light Control	ALC/ALC plus/ELC
Shutter	OFF (1/12.5), 1/25, 1/50, 1/60, 1/120, 1/250, 1/500, 1/1,000, 1/2,000, 1/4,000, 1/10,000 s
Motion Detector	ON/OFF selectable 4 areas
Auto Focus	Auto Back Focus
Back Light Compensation (BLC)	-
Sensitivity Enhancement	32x max. (AUTO or FIX)
White Balance	ATW1/ATW2/AWC
Adaptive Black Stretch	-

Camera Title	16 alphanumeric characters
Privacy Zone	ON/OFF (8 zone settings)
Image Stabilizer	ON/OFF
Colour/Mono Switching	AUTO1/AUTO2/EXT/ON/OFF
Language Setting	English, German, French, Italian, Spanish, Russian, Chinese, Japanese

Lens

Type	ALC lens drive, DC drive, CS-mount
Zoom Ratio	5x with digital zoom

Network

Network Interface	10Base-T/100Base-TX, RJ45 connector
Image Resolution	JPEG: 1,296 x 960 / VGA (640 x 480 pixels) / QVGA (320 x 240 pixels), MPEG-4 VGA (640 x 480 pixels) / QVGA (320 x 240 pixels)
Image Compression	MPEG-4: (Image quality: LOW/NORMAL/FINE), (Transmission type: UNICAST/MULTICAST), JPEG: (Image quality: 10 steps), (Transmission type: PULL/PUSH)
Image Refresh Rate	0.1 ips ~ 25 ips (Frame rate of JPEG will be limited when transmitting JPEG and MPEG-4 simultaneously)
Audio Compression	G.726 (ADPCM) 32 kbps / 16 kbps
Bandwidth Control	64 kbps/ 128 kbps/ 256 kbps/ 512 kbps/ 1,024 kbps/ 2,048 kbps/ 4,096 kbps/ unlimited
Supported Protocol	TCP/IP, UDP/IP, HTTP, FTP, SMTP, DHCP, DNS, DDNS, NTP, SNMP, RTP
Supported Operating System	Microsoft Windows 2000 Professional SP4, Microsoft Windows XP Home SP2, Microsoft Windows XP Professional SP2
Supported Browser	Internet Explorer 6.0 SP2 (Windows XP Home/Professional SP2), Internet Explorer 6.0 SP1 (Windows 2000 Professional SP4)
FTP Client	Alarm image transfer, periodic image transfer
Multi Screen	Images from 16 cameras can be displayed in 4 different Quad screens (JPEG only) or 16-screen (JPEG only)
SD Memory Card Slot	Manual REC/Alarm REC/Backup upon network failure. Compatible SD card: Panasonic 64MB, 128MB, 256MB, 512MB, 1GB, 2GB model. SD-HC standard card not supported.
Alarm Email	Yes
Time Date Display	-
Security Measures	-

Input/Output

Video Output	VBS: 1.0V [p-p]/ 75 Ohms composite signal, BNC connector
---------------------	--