



PRODUCT SPECIFICATION

PMCL15A Flat Panel, TFT LCD Monitor

15-INCH COLOR, HIGH RESOLUTION



Product Features


- High Resolution, 540 TV Lines (Composite Video Mode)
- Space-Saving, Flat Panel Design
- On-Screen Display for Setup and Adjustment of Monitor Parameters
- Multiple Video Inputs (Front Panel Switchable)
- PC Compatible Inputs
- Built-in Auto Input Scanning
- 90-260 VAC Input
- 50/60 Hz Auto Detection
- Built-in Speaker
- Video and Audio Input and Output

Pelco's **PMCL15A** thin film transfer (TFT) LCD panel has an overall depth of less than 3 inches (7.6 cm), making it ideal for security installations with limited space.

With a resolution of 540 TV lines, the **PMCL15A** produces a sharp picture. The LCD panel features dual video inputs for S-video and PC-based imaging to take full advantage of today's digital surveillance equipment.

PMCL15A's input circuitry supports NTSC/PAL formats and input voltages of 90-260 VAC. Efficiently designed, the unit consumes 60 percent less power than a conventional CRT monitor.

Other features include a long-life fluorescent backlight, built-in auto input scanning and on-screen display with multiple language capabilities. On-screen programmable image controls are adjustable using menu buttons conveniently located on the front panel of the unit.



NOTE: VALUES IN PARENTHESES ARE CENTIMETERS; ALL OTHERS ARE IN INCHES.





TECHNICAL SPECIFICATIONS

MODEL

PMCL15A High resolution 15-inch (38.1 cm)
TFT LCD flat panel

ELECTRICAL

Input Voltage 100-240 VAC, 50/60 Hz,
automatic switching
Power Consumption Maximum 35 watts
Input/Output Signal 1 Vp-p composite video signal
Input/Output Impedance 75 ohms
Scanning Frequency
NTSC 15750 Hz ± 500 Hz @ 60 Hz
PAL 15625 Hz ± 500 Hz @ 50 Hz
Connectors
Video Input/Output RCA
S-VHS Input 4-pin mini DIN
PC Input 15-pin connector
Audio Input/Output RCA
AC Power Cord Unit is supplied with two grounded
power cords; one for 120 VAC
and a "Euro"-style one for 230
VAC

GENERAL

Environment Indoor
Construction Black plastic
Finish Black matte texture coat finish
LCD Panel
Type 15-inch (38.1 cm) TFT color
Colors 16.7M colors
Viewable Size 12 (H) x 9 (V) inches
(30.48 x 22.86 cm)
Contrast Ratio 300:1
Brightness 350 cd/m²
Resident Resolution 1024 x 768
Dimensions
LCD Panel Only: 12.0" H x 15.4" W x 2.78" D
(30.48 x 39.05 x 7.11 cm)
LCD Panel with Base: 15.6" H x 15.4" W x 7.2" D
(39.5 x 39.05 x 18.3 cm)
Unit Weight 11.2 lb (5 kg)
Shipping Weight 16 lb (7.26 kg)

ENVIRONMENTAL

Operating
Temperature 50° to 104°F (10° to 40°C)
Humidity 20% to 85% (Non-condensation)

CERTIFICATIONS

- ◆ CE, Class B
- ◆ ETL listed to ANSI/UL 1950-1997
- ◆ cETL listed to CAN/CSA C22.2 No.950-95
- ◆ FCC, Class B