




Pyramid Series Proximity Readers

Pyramid Proximity Readers:


P- 300 Cascade Proximity Reader / Mullion Mount, 4" Read Range
 Includes Black and Off-White Covers / 1.5"W x 2.3"H x .49"D / 5-14VDC @ 80ma
P- 300-H is same as Doorframe reader above but with HID™ compatibility.



P- 400 Gibraltar Proximity Reader / Mullion Mount, UL752, 1" Read Range
 High Vandal Resistance Reader / 2"W x 5.25"H x .75"D / 5-14VDC @ 90ma
P- 400-H is same Stainless Steel & Fiber-Tex construction but with HID™ compatibility.



P- 500 Alps Proximity Reader / Wall Mount, 5" Read Range
 Includes Black and Off-White Covers / 3.0"W x 4.5"H x .38"D / 5-14VDC @ 80ma
P- 500-H is same as Single Gang reader above but with HID™ compatibility.



P- 600-8 Rocky Proximity Reader & Essex Keypad / 4" Read Range
 Includes Black and Off-White Covers / 3.9"W x 4.4"H x .95"D / 5-14VDC @ 90ma
 This Keypad has an 8 bit output for Card + PIN. The reader and keypad are controlled by the card reader and keypad time zones. The Time Zones determine when only a card is required, keypad is required, or both are required to gain entry. PIN numbers can be 4-7 digits.
For Card + PIN applications that require both a card read and keypad PIN
P- 600-8-H is same as the single piece reader & keypad above but with HID™ compatibility.



P- 600-26 Rocky Proximity Reader & Essex Keypad / 4" Read Range
 Includes Black and Off-White Covers / 3.9"W x 4.4"H x .95"D / 5-14VDC @ 90ma
 This Keypad has a 26 bit output for Card or PIN. The reader and keypad are controlled by the card reader Time Zone. At any time a card or a keypad code can be used but never are both required. Cards used should be 6 digits in length or greater and keypad codes can be 4 to 5 digits in length with a number no higher than 65534.
For Card or PIN applications that require either a card read or keypad PIN
P- 600-26-H is same as the single piece reader & keypad above but with HID™ compatibility.



P- 700 Yukon Medium Range Proximity Reader / 14" Bi-Directional Read Range
 Includes Black Cover / 6"W x 8.5"H x 1"D / 5-14VDC @ 285ma
P- 700-H is same Medium Range Reader as above but with HID™ compatibility.



-H Option for HID™ compatibility does not work for all HID Cards. It may be necessary to send a sample of cards to DSX for testing.