PROFESSIONAL



- Real-time display
- High performance recording, MPEG-4 compression
- True pentaplex operation: Record during Search, Playback, Setup, Backup, and when Networked
- USB mouse support
- Flexible backup: CD/DVD-RW, Memory stick, Network backup, USB HDD
- CMS (Central Monitoring System) software included
- Supports most popular PTZ protocols
- Self-diagnosis and notification of system status with S.M.A.R.T protocol
- Remote control included

Model	RDX824-500D	RDX1648-500D
Camera Inputs	8CH	16CH
HDD Size	500GB	500GB
Camera outputs	Composite, VGA, S-Video,Loopout, 2 Spot	
Compression	MPEG-4	
Recording Frame	240fps (200fps PAL)	480fps (400fps PAL)
Display Frame	270fps (225fps PAL)	480fps (400fps PAL)
Recording Resolution	720×480, 720×240, 360×240 (NTSC)	
OS	Embedded Linux	
Pentaplex	Live, Recording, Playback, Networking, Backup at the same time	
Sensor in / Alarm out	8in / 4out	16in / 4out
Audio	4 in / 1 out (G.723 Compression)	
Display Split	1,4,8	1,4,9,16
Digital Zoom	2X	
System Control	Front Buttons, Jog shuttle and IR Remote Controller, Mouse	
Features		
Recording Modes	Normal, Event, Always + Event, Sensor, Schedule	
Recording Quality	Lowest, Low, Normal, High, Highest (5 steps)	
Recording Resolution	720x480, 720x240, 360x240(NTSC)	
Search Mode	Date & Time, Calendar, Event(Motion, Sensor), First & Last	
PTZ Control	Pan/Tilt, Zoom, Focus, Iris, Preset	
Backup	CD/DVD-RW, 3 USB 2.0, USB HDD, Memory Stick	
Control Unit	IR Remote Control, Mouse Supported (mouse not included)	
Storage	Max. 4 HDD (factory installed)	
Upgrade	USB or Network (Firmup software)	
Network	10/100M Base-T Ethernet, LAN, WAN, Web, DHCP/DDNS, Static/Dynamic IP	
Remote Monitoring S/W	CMS, Callback Agent, Web viewer, PDA viewer	
Hardware		
Power	115/230VAC, 60/50Hz, 6/3A	
Dimensions (w/h/d)	17.1 × 3.4 × 16.7 inches (435 × 87 × 425 mm)	
Weight	Approx 17.6 lbs. (8kg)	

