

RC6602HD-5311

H.264 Full HD Indoor / Outdoor IR Bullet IP Camera

- Full Frame at HD1080p
- Remote Zoom/Focus Control (One Click AF)
- Video Compression: H.264, MJPEG
- Dual Stream
- Burnt-in Text, Video Motion Detection Support
- Two-way Audio with G.711
- microSD Memory Support
- Remote Firmware Upgrade over Network
- Comprehensive SDK Support
- Embedded Video Analytics



Specifications

Camera Module	
Image Sensor	1/2.7" 1080p CMOS
Effective Pixels	1920 x 1080
Scanning System	Progressive scanning
AGC Control	Auto
Minimum Illumination	Color: 1.0 lux, F1.2 BW: 0.00 lux (IR LED On)
Lens	3.0 – 9.0mm Vari-Focal F1.2 Remote Zoom/Focus Control (One Click AF)
Day & Night	IR Cut Filter Removal
Smart Edge Enhance	Supported (Auto adjust the sharpness by Lux)
2D-DNR	Supported (1 – 16)
DSS (Sens-up)	2X – 32X
White Balance	ATW / Manual / Push
BLC	On (possible to designate zone), Off
IR LEDs	38 IR LEDs
IR Range	Internal Use : 25m, External Use : 15m
Iris	DC Auto Iris
Video	
Compression Format	H.264, MJPEG
Number of Streams	Dual Stream, Configurable
Resolution	1920x1080, 1280x720, 800x450, 480x270, 320x180
Compression FPS	Configurable up to 30fps@1080p
Motion Detection	Built-in
Burnt-in Text	Video stream overlay text
Output	Analog video output for installation only
Audio	
Input	1 channel
Output	1 channel
Compression Format	G.711
Function	
Digital Input	1
Digital Output	1
Network	10 / 100 Base-T
Protocol	TCP/IP, UDP/IP, HTTP, RTSP, RTCP, RTP/UDP, RTP/TCP, SNTP, mDNS, UPnP, SMTP, SOCK, IGMP, DHCP, DDNS, SSL v2/v3, IEEE 802.1X, SSH, SNMP v2/v3
SD Memory Card Slot	1 MicroSD

Electrical	
Power Source	12V DC
Power over Ethernet	Support (PoE, IEEE 802.3at)
Power Consumption (Approx)	900mA @ DC 12V (IR, Fan & Heater On)
Environmental	
Fan / Heater	Fan / Heater Unit
Operation Temperature	DC12V : -40°C ~ 50°C (-40°F ~ 122°F) PoE : 0°C ~ 50°C (32°F ~ 122°F) Cold Start DC12V : -20°C (-4°F) PoE: 0 °C (32°F)
Operating Humidity	Up to 85% RH, Non-condensing
Mechanical	
Material	Aluminum Die Casting
Color	White
Dimension	83(W) x 82(H) x 194(D) mm
Weight (Approx)	1.5kg

Please Note: Datasheet Primarily Version