

Super High-Resolution DayNight Dome Camera

SCC-B5331/B5333 SCC-B5335

NEW



Features

- 1/3" SONY 410K/470K Pixels Super-HAD IT CCD
- High Resolution : 600 TV Lines
- Min. illumination 0.0006Lux (F2.0, 15 IRE, Sens-Up 512x)
 SCC-B5331 : f=3.8 mm, Fixed Iris Lens
 SCC-B5333 : f=3.0 mm, Fixed Iris Lens
 SCC-B5335 : f=8.0 mm, Fixed Iris Lens
- Internal/LineLock (Phase Control) Function
- Day/Night Function (Soft), Sens-Up Function (512x)
- Motion Adaptive Digital Noise Reduction (3D+2D)
- Back Light Compensation (Area Setting)
- Advanced Motion Detection Function
- eXtended Dynamic Range (XDR)
- Privacy Mask Function (Polygonal Mosaic)
- DIS (Digital Image Stabilization)
- CCVC (Camera Control Via Coaxial cable, Controller : SCX-RD100)
- Intelligent Video (Moved / Fixed / Fence / Area / Tracking)
- Multi-Language OSD support
- DC12V & AC24V 60Hz/50Hz

Specifications

Model	SCC-B5331	SCC-B5333	SCC-B5335		
Camera Type	Color				
Image	Device	1/3" Super-HAD IT CCD			
	Pixels	Effective	768 x 494 / 752 x 582		
Scanning	System		Interlace		
	Horizontal	Internal Mode	15,734 Hz / 15,625 Hz		
		Line-lock Mode	15,750 Hz / 15,625 Hz		
	Vertical	Internal Mode	59.94 Hz / 50 Hz		
Line-lock Mode		60 Hz / 50 Hz			
Resolution	Horizontal	600 TV Lines			
Min. Scene Illumination	Sens-up off	0.3Lux(15IRE), 0.6Lux(30IRE), 1.0Lux(50IRE) @F2.0			
	Sens-up	0.0006Lux(15IRE), 0.0012Lux(30IRE), 0.002Lux(50IRE) @F2.0			
Functions	Number of Privacy Zone	12 (Polygonal Method)			
	Day/Night	Color/BW/AUTO(Soft)			
	Motion Detection	Off/On			
	D-Zoom	1x ~ 16x (0.1x STEP)			
	Sens Up	2x ~ 512x			
	BLC / AGC	Off/On / Off/On			
	ELC	Off/On (~ 1/200Ksec)			
	Line Lock	Off/On (Phase Control)			
	Camera ID	Off/On (Max.54ea/2Lines)			
	White Balance	ATW1/ATW2/AWC/MANUAL			
	eXtended Dynamic Range	Off/Low/Mid/High			
	Digital Noise Reduction	Off/On			
	Digital Image Stabilization	Off/On			
	Intelligent Video	Off/On (Moved / Fixed / Fence / Area / Tracking)			
	PIP	Off/On			
	Etc. Function	Detail, Reverse(H/V), Posi/Nega			
Video Output	VBS 1.0Vp-p	VBS 1.0VpN/Ap			
S/N Ratio	52 dB				
Lens	Focal Length	f=3.8 mm	f=3.0 mm	f=8.0 mm	
	Aperture Ratio	F2.0			
	Viewing Angle	Wide	71°(H) x 53°(V)	92°(H) x 72°(V)	72°(H) x 25.3°(V)
	Lens Drive Type / Mount Type		MANUAL / Board Type		
OSD	Yes				
Remote Control	CCVC	Yes (with SCX-RD100)			
Environmental Conditions	Operating Temperature	Absolute : -10°C ~ +50°C / Sustained : -20°C ~ +60°C			
	Operating Humidity	Less than 90%			
Power	Power Requirement	24 VAC ±10%/12 VDC ±10%			
Physical	Dimensions(WxHxD)	102(ø) x 78(H) mm			
Specification	Weight	220 g			
	Color	Body	Silver		

Dimensions (unit:mm)

