

Super High-Resolution DayNight Dome Camera

SCC-B5366/B5368 NEW



Features

- 1/3" SONY 410K/470K Pixels Super-HAD IT CCD
- High Resolution : 600 TV Lines
- Min. illumination 0.00023Lux (F1.2, 15 IRE, Sens-Up 512x)
- SCC-B5366 : f=2.5~6 mm, Auto Iris Lens
SCC-B5368 : f=2.8~11 mm, Auto Iris Lens
- Internal/Linelock (Phase Control) Function
- Day/Night Function (Soft), Sens-Up Function (512x)
- Motion Adaptive Digital Noise Reduction (3D+2D)
- Back Light Compensation (Area Setting)
- Advanced Motion Detection Function
- eXtended Dynamic Range (XDR)
- Privacy Mask Function (Polygonal Mosaic)
- DIS (Digital Image Stabilization)
- CCVC (Camera Control Via Coaxial cable, Controller: SCX-RD100)
- Multi-Language OSD support
- Intelligent Video (Moved / Fixed / Fence / Area / Tracking)
- DC12V & AC24V 60Hz(50Hz)

Specifications

Model	SCC-B5366	SCC-B5368		
Camera Type	Color/BW			
Image	Device	Color		
	Pixels	Effective		
Scanning	System	Interlace		
	Horizontal	Internal Mode	15,734 Hz / 15,625 Hz	
		Line-lock Mode	15,750 Hz / 15,625 Hz	
	Vertical	Internal Mode	59.94 Hz / 50 Hz	
Line-lock Mode		60 Hz / 50 Hz		
Resolution	Horizontal	600 TV Lines		
Min. Scene Illumination	Sens-up off	0.12Lux(15 IRE), 0.2Lux(30 IRE), 0.4Lux(50 IRE) @F1.2		
	Sens-up	0.00023Lux(15 IRE), 0.0005Lux(30 IRE), 0.0008Lux(50 IRE) @F1.2		
Functions	Number of Privacy Zone	12 (Polygonal Method)		
	Day/Night	Color/BW/AUTO (Soft)		
	Motion Detection	Off/On		
	Wide Dynamic Range	Off/On (128x)		
	D-Zoom	1x ~16x (0.1x STEP)		
	High Speed Shutter	1/60~1/10Ksec(OSD)	1/50~1/10Ksec(OSD)	
	Sens Up	2x ~ 512x		
	BLC / AGC	Off/On / Off/On		
	Line Lock	Off/On (Phase Control)		
	Camera ID	Off/On (Max.54ea/2Lines)		
	White Balance	ATW1/ATW2/AWC/MANUAL		
	eXtended Dynamic Range	Off/Low/Mid/High		
	Digital Noise Reduction	Off/On		
	Digital Image Stabilization	Off/On		
	Intelligent Video	Off/On (Moved / Fixed / Fence / Area / Tracking)		
PIP	Off/On			
Etc. Function	Detail, Reverse(H/V), Posi/Nega			
Video Output	VBS 1.0Vp-p	VBS 1.0VpN/Ap		
S/N Ratio	52 dB			
Lens	Focal Length	2.5~6mm	2.8~11mm	
	Aperature Ratio	F1.2		
	Viewing Angle	Tele	46°(H) x 34°(V)	28.8°(H) x 21.6°(V)
		Wide	108°(H) x 80°(V)	94.6°(H) x 68.4°(V)
	Lens Drive Type / Mount Type	AI(DC) / Board Type		
Remote Control	CCVC	Yes (with SCX-RD100)		
	RS485	Yes (Multi Protocol, 8ea)		
Environmental Conditions	Operating Temperature	Absolute : -10°C ~ +50°C / Sustained : -20°C ~ +60°C		
	Operating Humidity	Less than 90%		
Power	Power Requirement	24 VAC ±10%/12 VDC ±10%		
Physical Specification	Dimensions	102(ø) x 78(H) mm		
Weight	Weight	330 g		
	Color	Body	White	

Dimensions (unit:mm)

