

Video Security Systems


SDM-160MP

Specifications

MODEL	SDM-160MP	
Video Input	Camera	16Ch Input(Black and /White), BNC Type, Looped Through Out, 1.0Vp-p, 75 Auto-Termination Type
	VCR	Composite : BNC Type S-VHS Y/C - Y : 1.0Vp-p, 75 Termination - C : 0.3Vp-p, 75 Termination
Video Output	2Ch Output(Composite) Main Monitor - Full, Full Screen Auto Switching, Full Screen Freeze, Full Screen x2, x4 Zoom - Live Division of Screen(Dual_H,Dual_V, 4, 7, 9, 10, 13, 16, PIP), Freeze Division Screen(4, 9 division) Automatic Switching(Bottom of Right) - PB Screen(Dual_H,Dual_V,4,7,9,10,13,16,Full Screen Freeze, Full Screen x2, x4 Zoom) - REC Check Output - PB Through Output - Live, PB Simultaneous Division Screen(2, 4, 9, 16) - Real Time Display of Quad Screen Spot Monitor - Certain Screen Monitoring(Full Screen)	
Record Output	Frame/Field selection & Duty setting per channel	
Remote Control	- RS-485 : Modular Jack - RS-232C : D-Sub 9Pin	
Alarm Input	16Ch Input Terminal Block	
Alarm Output	- Relay Out : 2 - Reset Out : 1	
Alarm Loss List Memory	100 Event	
Motion Detection	16Ch	
Motion Detection Weight Value Recording	Yes (Upon motion detection, recording output of the Motion channel is weighed)	
Summer Time Mode	Menu method	
Horizontal Resolution	400 TV Lines	
VCR Trigger	1Ch	
Operating Temperature	0 ~ +40	
Operating Humidity	20 ~ 85%RH	
Power Requirement	AC100~240V, 50/60Hz	
Power Consumption	Less than 14W	
Weight	Approx. 5.0Kg(without packing)	
Dimensions(W x H x D)	430 x 88 x 350mm	



Dimensions



Conform to Korean EMC (SEMI) 100 VDR, Argentina

ISO9001 : 1994
File No. : A8150



Samsung Headquarters
Samsung Electronics Co., Ltd.
416, Maetan-3Dong, Paldal-Gu
Suwon City, Kyungki-Do, Korea 442-742
TEL : 82-31-200-5504, 5578 FAX : 82-31-200-5594
<http://samsungelectronics.com/security/cctv/>

Distributed by:

* Design and specifications are subject to change without notice.