

16Ch Multiplexer

SDM-160P



Features

- 400 TV lines of horizontal resolution
- Triplex function
- Simultaneous display of VCR replay and live camera feed on a single monitor during recording.
- To be used with a S-VHS recorder for high quality recording
- Various screen display function
 - Full screen auto switching, Full screen freeze, Full screen zoom
 - Live division screen(Dual_H,Dual_V, 4, 7, 9, 10, 13, 16, PIP),Freeze
 - Automatic screen switching on the lower right screen in 4 or 9 screen mode.
 - P.B screen
 - (Dual_H,Dual_V,4,7,9,10,13,16,Full screen freeze, Full screen x2, x Zoom)
 - P.B Through output
 - Live, P.B simultaneous division screen(2,4,9,16)
- Recording output : selectable frame/field, recording duty time varies by channel list
- Buzzer : In time of alarm, Video loss, Motion occurrence
- Real time display function(Quad screen)
- Motion detection function
- Summer time observation function
- Trigger detect function
- (Automatic switching to field recording mode during no trigger)
- Alarm/Loss list 100event
- Timer Recording function
- Security lock function
- Alarm weight value recording function
- Motion detection weight value recording function
- RS-232C, RS-485 remote control


Video Security Systems

SDM-160P

Specifications

MODEL	SDM-160P	
Video Input	Camera	16Ch Input(Color, Black and /White), BNC Type, Looped Through Out, 1.0Vp-p, 75 Auto-Termination Type
	VCR	Composite : BNC Type S-VHS Y/C - Y : 1.0Vp-p, 75 Termination - C : 0.3Vp-p, 75 Termination
Video Output	3Ch Output(Composite 2 Output, S-VHS 1 Output) Main Monitor - Full, Full Screen Auto Switching, Full Screen Freeze, Full Screen x2, x4 Zoom - Live Division of Screen(Dual_H,Dual_V, 4, 7, 9, 10, 13, 16, PIP),Freeze Division Screen(4,9 division) Automatic Switching(Bottom of Right) - PB Screen(Dual_H,Dual_V, 4, 7, 9, 10, 13, 16, Full Screen Freeze, Full Screen x2, x4 Zoom) - REC Check Output - PB Through Output - Live, PB Simultaneous Division Screen(2, 4, 9, 16) - Real Time Display of Quad Screen Spot Monitor - Certain Screen Monitoring(Full Screen) S-VHS - at the same of Main Monitor	
Remote Control	- RS-485 : Modular Jack - RS-232C : D-Sub 9Pin	
Alarm Input	16Ch Input Terminal Block	
Alarm Output	- Relay Out : 2 - Reset Out : 1	
Alarm Loss List Memory	100 Event	
Motion Detection	16Ch	
Summer Time Mode	Menu method	
Horizontal Resolution	400 TV Lines	
VCR Trigger	1Ch	
Operating Temperature	0 ~+40	
Operating Humidity	20~85%RH	
Power Requirement	AC100~240V, 50/60Hz	
Power Consumption	Less than 14W	
Weight	Approx. 5.0Kg(without packing)	
Dimensions(W x H x D)	430 x 88 x 350mm	

Dimensions



SAMSUNG

ELECTRONICS

Samsung Headquarters

Samsung Electronics Co., Ltd.

416, Maetan-3Dong, Paldal-Gu

Suwon City, Kyungki-Do, Korea 442-742

TEL : 82-31-200-5504, 5578 FAX : 82-31-200-5594

<http://samsungelectronics.com/security/cctv/>

Distributed by:

* Design and specifications are subject to change without notice.