

NEW

# SHB-4300H/4300H1 4300H2

Housing for Fixed Camera



## Features

- SHB-4300H** Indoor/Outdoor Housing
  - For fixed camera application
  - Aluminum diecasting construction
  - Fully cable managed bracket
  - De-mister heater, fan
  - Support three cable glands
  - 24V AC
- SHB-4300H1** Extreme weather proof housing
  - For fixed camera application
  - Aluminum diecasting construction
  - Fully cable managed bracket
  - De-mister heater, fan
  - Support three cable glands
  - 24V AC
- SHB-4300H2** Extreme weather proof housing
  - For fixed camera application
  - Aluminum diecasting construction
  - Fully cable managed bracket
  - De-mister heater, fan
  - Support three cable glands
  - 230V AC

## Technical Specifications

		SHB-4300H	SHB-4300H1	SHB-4300H2
Open Type		Side open	Side open	Side open
Cable Entry		Nylon gland	Nylon gland	Nylon gland
Operating Temperature		-35°C ~ +50°C (-22°F ~ +122°F)	-50°C ~ +50°C (-58°F ~ +122°F)	-50°C ~ +50°C (-58°F ~ +122°F)
Operating Temperature	Heater	5°C ± 5°C on	5°C ± 5°C on	5°C ± 5°C on
	Blower	+45°C ~ +5°C on	+45°C ~ +5°C on	+45°C ~ +5°C on
Operating Temperature	Defroster	N/A	Constant	Constant
	Operating Humidity	-20% ~ 49% RH	-20% ~ 49% RH	-20% ~ 49% RH
Materials		Aluminum	Aluminum	Aluminum
Ingress Protection		IP66	IP66	IP66
Color		Ivory	Ivory	Ivory
Dimensions (WxHxD)	External	184 x 127 x 460mm (7.24" x 5" x 18.11")	184 x 127 x 460mm (7.24" x 5" x 18.11")	184 x 127 x 460mm (7.24" x 5" x 18.11")
	Internal	100 x 80 x 383mm (3.94" x 3.15" x 15.08")	100 x 80 x 383mm (3.94" x 3.15" x 15.08")	100 x 80 x 383mm (3.94" x 3.15" x 15.08")
Weight		3.5Kg (7.72 lb)	3.7Kg (8.16 lb)	3.7Kg (8.16 lb)
Certificate		CE (Class A)	CE (Class A)	CE (Class A)

## Dimensions

Unit : mm (inch)

