



For your professional monitoring



17" TFT LCD Monitor

SMT-1712/1722/1723



- Support up to 1280 x 1024 resolution
- Dynamic contrast 1000 : 1
- Fast response time 5ms
- Durable tempered glass screen

17" TFT LCD Monitor

SMT-1712/1722/1723




Specifications

		SMT-1712	SMT-1722	SMT-1723
DISPLAY				
Screen Size		17"		
Max. R resolution		1,280 x 1,024 @60Hz	1,280 x 1,024 @120Hz	
Brightness		250cd/m ²		
Contrast Ratio		1,000 : 1		
Aspect Ratio		4 : 3		
Viewing Angle (H/V)		160° / 160°		
Display Color		16.7Million		
Response Time		5ms		
Video System		NTSC / PAL		
Panel Life		50,000 hours		
Filter Type		N/A	3D Combfiter	
INTERFACE				
Video	Connector	N/A	BNC types : (2 in/2 out)	
S-Video	Connector	N/A	1CH input (Y/C), Loop Through out	
	Connector	One(1) Analog RGB 15-pin D-sub		
	Input signal	0.7 Vp-p (0.5-1 Vrms)		
RGB	Available Format	640 x 350@70 Hz	720 x 400@70 Hz	
		720 x 400@70 Hz	720 x 400@70 Hz	
		640 x 480@60 Hz / 72 Hz / 75 Hz (VGA)	640 x 480@60 Hz / 72 Hz / 75 Hz (VGA)	
		800 x 600@56 Hz / 60 Hz / 72 Hz / 75 Hz (SVGA)	800 x 600@56 Hz / 60 Hz / 72 Hz / 75 Hz (SVGA)	
		1,024 x 768@60 Hz / 70 Hz / 75 Hz (XGA)	1,024 x 768@60 Hz / 70 Hz / 75 Hz (XGA)	
		1,152 x 864@75 Hz	1,152 x 864@75 Hz	
		1,280 x 720@60 Hz	1,280 x 720@60 Hz	
		1,280 x 960@60 Hz	1,280 x 960@60 Hz	
		1,280 x 1,024@60 Hz / 75 Hz (SXGA)	1,280 x 1,024@60 Hz / 75 Hz (SXGA)	
HDMI	Connector	N/A		
	Available Format	N/A		
Audio	Connector	N/A	Two(2) RCA type (2 stereo inputs)	
	Output signal	Loud Speakers : two(2) x 1 W		
Application Support		Remote Controller		
ON SCREEN DISPLAY				
Functions		VESA™ DPM Compatible	Motion technology(120Hz), VESA™ DPM Compatible, PIP/PBP	
Language		English, Spanish, French, German, Italian, Portuguese, Russian, Swedish, Chinese, Japanese, Korean		
GENERAL				
Electrical	Input Voltage	AC100 ~ 240V (50/60Hz)		12V DC (External power supply)
	Power consumption	Type 22W	Type 34W	Type 31W
Environmental	Operating Temperature	0 ~ +40°C (+32°F ~ +104°F)		
	Humidity	10% ~ 80% (non-condensing)	20% ~ 90% (non-condensation)	
Mechanical	Dimensions with Stand (WxHxD)	371 x 404 x 217 mm (14.61" x 15.91" x 8.54")	371 x 368 x 220 mm (14.61" x 14.49" x 8.66")	
	Dimensions without Stand (WxHxD)	371 x 331 x 70 mm (14.61" x 13.03" x 2.76")	371 x 331 x 67 mm (14.61" x 13.03" x 2.64")	
	Weight	4.9kg (10.8lbs)	5.95kg (13.12lbs)	
	LCD Protection Glass	Yes		
	Cabinet Color	Black		
VESA Mounts Interface		100 x 100mm		

Dimensions

Unit : mm (inch)



Design and specifications are subject to change without notice.



The Eco mark represents Samsung Techwin's will to create environment-friendly products, and indicates that the product satisfies the EU RoHS Directive.



SAMSUNG TECHWIN CO., LTD.

701, Sampyeong-dong, Bundang-gu, Seongnam-si, Gyeonggi-do Korea 463-400
Tel : +82-70-7147-8741-8749, 8752-8760 Fax : +82-31-8018-3745
www.samsungsecurity.com www.samsungcctv.com

SAMSUNG TECHWIN AMERICA INC.
1480 Charles Willard St. Carson, CA 90746, UNITED STATES
Tel Free : +1-877-213-1222 Fax : +1-310-632-2195
www.samsungcctvusa.com

SAMSUNG TECHWIN EUROPE LTD.
Samsung House, 1000 Hillwood Drive, Hillwood Business Park
Chertsey, Surrey, UNITED KINGDOM KT16 OPS
Tel : +44-1932-45-5300 Fax : +44-1932-45-5325

TIANJIN SAMSUNG TECHWIN OPTO-ELECTRONICS CO., LTD.
No.11 Wei 6 Street, Micro-Electronic Industrial Park
Jingang Road, Tianjin, P.R. CHINA 300385
Tel : +86-22-23887788 Fax : +86-22-23887788

■ DISTRIBUTED BY

