

SNM-64P

Centralized Video Management Software

Technical Specifications

		SNM-64P (Professional)
Device to Use	Supported Devices	Network Camera : SNC-570/550, SNP-3300A/1000A Video Encoder : SNS-400/100 DVR : SVR-1650E/1645/1640A/950E/940/450
	Max. Register Device	No limit
Live Monitoring	Multi-monitor	Max. 3 (Live 2)
	Screen-split Modes	1 / 4 / 6 / 8 / 9 / 16 / 25 / 36 / 49 / 64 (Full-screen)
	Launches Instant Player	DVR only
	Controls PTZ Function	Pan, Tilt, Zoom, Focus, Preset
	FTP/E-mail Notification	Supported
	Snapshot / Prints Image	Supported
Playback	Local (Remote) Playback / Back up	Supported
	Converts Video Format	AVI
	Search	Go to a certain time, Latest data search, Timeline index search, Thumbnail image search
	Zooms in/out on the Image	Supported
	Snapshot / Prints Image	Supported
Event Signal Monitoring	Display	Current event log on the list, live image, Changes border of live video channel to red
	Filtering	Unnecessary signal
	Event image Playback	DVR only
Alarm Signal Monitoring	Displays	Current alarm log on the list, Live/thumbnail image
	Set up	A certain period of time of a day, A certain types of alarms Automated notifications to user, Schedules actions against alarms
	Event Image Playback	DVR only
	Controls Preset on PTZ Camera	Supported
	Plays Warning Sound or Message	Supported
	FTP/E-mail Notification	Supported
	Marks an Alarm as Confirmed	Supported
Provides Space to Write Comments	Supported	
User	Group / User	Group / user : No limit
	Number of Map	Map group : No limit, Layers : 16, Maps : 64
MAP	Supports Image	JPEG / BMP
	System Specifications	CPU : Intel Core2Duo E4300, RAM : 2GB above Video memory : 256MB, HDD : 80GB OS : Window 2000/XP SP2, DirectX 9.0 above Display resolution : 1,024 x 768 above