

# Industrial/Installation TFT LCD Video Monitors



LMU-TK15C4  
LMU-TK20C1

Flat screen monitors designed for quality installations in consoles, lecturns, kiosks or for wall mounting.

Perfect for retail display, museums, CCTV control rooms, public information displays and any applications requiring high quality video but where space is limited.

- High quality industrial LCD flat screen video monitors
- Space saving
- 15" and 20" versions
- Tough metal casing
- Composite video, S-Video and data inputs
- Low power consumption, heat emission and no electromagnetic radiation



**SANYO**

# High quality video where space is limited



## LMU-TK15C4

- 15" LCD monitor with video and data inputs
- XGA resolution (1024 x 768) TFT active matrix LCD panel
- Automatic set-up and adjustment
- Space saving - only 46mm deep
- Wired remote control



## LMU-TK20C1

- 20" LCD Monitor with video and data inputs
- High brightness 500 cd/m<sup>2</sup>
- Automatic set-up and adjustment
- Space saving - only 49mm deep
- VGA (640 x 480) data resolution
- Wired remote control

Dealer:

## LMU-TK15C4 SPECIFICATIONS

|                             |                                                   |
|-----------------------------|---------------------------------------------------|
| Model Name                  | LMU-TK15C4                                        |
| Screen Size                 | 15"                                               |
| Number of Pixels            | 1024 x 768                                        |
| Pixel Pitch                 | 0.297mm x 0.297mm                                 |
| Viewable area               | 304.1mm x 228.1mm                                 |
| Brightness                  | 250 cd/m <sup>2</sup>                             |
| Contrast ratio              | 350:1                                             |
| Viewing Angle               | Up/down 60°, left/right 70°                       |
| Colours                     | 16.77 million                                     |
| Power Consumption           | 34W                                               |
| Terminals-video             | Composite video (RCA x 1), S-Video (mini DIN4)    |
| Terminals-data              | 15 pin mini D-sub                                 |
| AC adaptor                  | Input 115-240V AC 50/60Hz, Output 12V DC 2.5A     |
| Power Management            | VESA DPMS                                         |
| Plug and Play               | VESA DDC1 & DDC2B                                 |
| Synchronization frequencies | Vertical 56 - 75 Hz<br>Horizontal 24.8 - 60.2 kHz |
| Video systems               | PAL/NTSC                                          |
| Dimensions (W x H x D)      | 384 x 308 x 46mm                                  |
| Weight                      | 3.8kg                                             |

## LMU-TK20C1 SPECIFICATIONS

|                             |                                                   |
|-----------------------------|---------------------------------------------------|
| Model Name                  | LMU-TK20C1                                        |
| Screen Size                 | 20.1"                                             |
| Number of Pixels            | 640 x 480                                         |
| Pixel Pitch                 | 0.6375mm x 0.6375mm                               |
| Viewable area               | 408mm x 306mm                                     |
| Brightness                  | 500 cd/m <sup>2</sup>                             |
| Contrast ratio              | 400:1                                             |
| Viewing Angle               | Up 55°, down 50°, left/right 65°                  |
| Colours                     | 16.19 million                                     |
| Power Consumption           | 73W                                               |
| Terminals-video             | Composite video (RCA x 1), S-Video (mini DIN4)    |
| Terminals-data              | 15 pin mini D-sub                                 |
| AC adaptor                  | Input 100-240V AC 50/60Hz, Output 16V DC 5A       |
| Power Management            | VESA DPMS                                         |
| Plug and Play               | VESA DDC1 & DDC2B                                 |
| Synchronization frequencies | Vertical 56 - 75 Hz<br>Horizontal 24.8 - 37.8 kHz |
| Video systems               | PAL/NTSC                                          |
| Dimensions (W x H x D)      | 459 x 359 x 62mm                                  |
| Weight                      | 5.0kg                                             |

Both units have standard VESA fixings, allowing the use of a wide variety of brackets and arms.

# SANYO

Commercial Division. Sanyo UK Sales, Sanyo House,  
Otterspool Way, Watford, Herts WD25 8JX  
Telephone: 01923 477220 Fax: 01923 477225 [www.sanyo.co.uk](http://www.sanyo.co.uk)

Whilst every care is taken to ensure that the details in this leaflet are correct at time of going to press, they are intended as a guide only and do not constitute an offer. Because Sanyo's policy is one of continuous improvement, it is possible that alterations to specifications may have occurred since printing. For clarification on any point, please contact your local appointed dealer, or write to Sanyo at the address shown.