

**SNCA-HRX550EXT-W**

**Outdoor wireless dome camera housing**



Applicable Camera Models;  
- SNC-RX550P - SNC-RX530P - SNC-RX570P

Fixing Method;  
- SNCA-WM20G (wall) - SNCA-CEILING (ceiling) -  
SNCA-WM20FC (see note)

Rating;  
- IP66

Operating Temperature;  
- -29°C to +50°C - -44°C to +50°C with optional  
heater/blower kit added (SNCA-HEATER)

Voltage;  
- 24 volts AC

Optional accessories;  
- SNCA-CLEAR/2 (included) - SNCA-TINTED/2 -  
SNCA-HEATER

## Accessories

### Mounting Hardware

**SNCA-WM20FC**

Wall mount for dome camera housings with fixed coupling attached

**SNCA-CEILING**

Mounting coupling for pendant applications

**SNCA-WM20G**

Wall mount for dome camera housings

**SNCA-POLE30**

Mounting pipe for pendant mount applications

### Power supplies

**SNCA-PS24-4**

An indoor power supply with one 4 Amp 24V AC fused output.

**SNCA-PS24-4E**

An external power supply with one 4 Amp 24V AC fused output. Polycarbonate IP66 rated enclosure suitable for outdoor use.

## Compatible Products

### Pan Tilt Zoom

**SNC-RX530P**

Intelligent Network Camera with 216x zoom  
- Black

**SNC-RX550P/WCE**

Intelligent Network Camera - White

**SNC-RX550P/BC**

Intelligent Network Camera with 312x zoom  
- Black

**SNC-RX570P**

Intelligent Network Camera with DynaView  
and 432x zoom- Black