



Model	Indoor Mini Dome IR FIX DOME						Indoor Dome DOME	Outdoor Dome IR FIX DOME
	SSC-YM401R	SSC-YM411R	SSC-YM501R	SSC-YM511R	SSC-CM461R	SSC-CM561R	SSC-CR481	SSC-CM565R
Image device	1/3" 760H Super HAD CCD II	1/3" 760H Super HAD CCD II	1/3" 960H ExView HAD CCD II	1/3" 960H ExView HAD CCD II	1/3" 760H Super HAD CCD II	1/3" 960H ExView HAD CCD II	1/4" ExView HAD CCD	1/3" 960H ExView HAD CCD II
Day/Night	Electrical D/N	Electrical D/N	Optical D/N	Optical D/N	Optical D/N	Optical D/N	Optical D/N	Optical D/N
Number of effective pixels	Approx. 440,000 pixels 752 (H) x 582 (V)	Approx. 440,000 pixels 752 (H) x 582 (V)	Approx. 570,000 pixels 976 (H) x 582 (V)	Approx. 570,000 pixels 976 (H) x 582 (V)	Approx. 440,000 pixels 752 (H) x 582 (V)	Approx. 570,000 pixels 976 (H) x 582 (V)	Approx. 440,000 pixels 752 (H) x 582 (V)	Approx. 570,000 pixels 976 (H) x 582 (V)
Horizontal resolution	540 TVL	540 TVL	660 TVL	650 TVL	540 TVL	700 TVL (Sharp mode) 650 TVL (Normal mode)	550 TVL	700 TVL (Sharp mode) 650 TVL (Normal mode)
Vandal Resistant	-	-	-	-	-	-	-	IK09
Ingress Protection	-	-	-	-	-	-	-	IP66
Minimum Illumination Color	50 IRE 0.06 lx	0.06 lx	0.06 lx	0.06 lx	0.06 lx	0.06 lx	1.4 lx	0.06 lx
Minimum Illumination B/W	30 IRE 0 lx	0 lx	0 lx	0 lx	0 lx	0 lx	0.9 lx	0.04 lx
Minimum Illumination Condition	F2.0 AGC ON	F1.8 AGC ON	F2.0 AGC ON	F1.8 AGC ON	F1.2 AGC ON	F1.2 AGC ON	F1.6 AGC ON	F1.2 AGC ON
Signal system	PAL	PAL	PAL	PAL	PAL	PAL	PAL	PAL
Video output	VBS:1.0Vp-p	VBS:1.0Vp-p	VBS:1.0Vp-p	VBS:1.0Vp-p	VBS:1.0Vp-p	VBS:1.0Vp-p	VBS:1.0Vp-p	VBS:1.0Vp-p
S/N ratio	More than 55 dB	More than 55 dB	More than 55 dB	More than 55 dB	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)	More than 50 dB (Weight: ON)	More than 55 dB (AGC Off)
Synchronization	Internal Only	Internal Only	Internal Only	Internal Only	Internal/AC line lock selectable	Internal/AC line lock selectable	Internal/AC line lock selectable	Internal/AC line lock selectable
Gain control	Auto	Auto	Auto	Auto	Auto (on/off)	Auto (on/off)	Auto/Manual	Auto (on/off)
Shutter Speed	Auto	Auto	Auto	Auto	Fixed (1/50 s)	Fixed (1/50 s)	1/1 sec - 1/10000 sec	Fixed (1/50 s)
White balance	ATW (2000K-10000K)	ATW (2000K-10000K)	ATW (2000K-10000K)	ATW (2000K-10000K)	ATW (2000K-10000K), ATW-pro (2500K-6000K)	ATW (2000K-10000K), ATW-pro (2500K-6000K)	ATW/Auto/One Push/ Indoor/Outdoor/ Sodium Lamp/Manual	ATW (2000K-10000K), ATW-pro (2500K-6000K)
Lens type	Mono-focal type	Mono-focal type	Mono-focal type	Mono-focal type	Vari-focal type	Vari-focal type	Auto-focus zoom lens	Vari-focal type
Lens Mount	-	-	-	-	-	-	-	-
Focal Length	f = 3.1 mm	f = 6 mm	f = 3.1 mm	f = 6 mm	f = 2.8 to 10.5 mm	f = 2.8 to 10.5 mm	f = 3.4 to 122.4 mm	f = 2.8 to 10.5 mm
Zoom Ratio	-	-	-	-	Optical 3.7 x	Optical 3.7 x	Optical 36x, Digital 12x	Optical 3.7 x
F number	F2.0	F1.8	F2.0	F1.8	F1.2 (Wide), F2.7 (Tele)	F1.2 (Wide), F2.7 (Tele)	F1.6 (Wide), F4.5 (Tele)	F1.2 (Wide), F2.7 (Tele)
Angle of View (H)	96.3 degree	46.5 degree	96.3 degree	46.5 degree	101.8 to 27.4 degree	101.8 to 27.4 degree	57.8 to 1.7 degree	101.8 to 27.4 degree
Panning range	355 degree	355 degree	355 degree	355 degree	355 degree	355 degree	360 degrees endless rotation	355 degree
Tilting range	±66 degree	±66 degree	±66 degree	±66 degree	±66 degree	±66 degree	210 degrees	±77 degree
Swivel range	350 degree	350 degree	350 degree	350 degree	350 degree	350 degree	-	350 degree
Minimum object distance	0.4 M	0.8 M	0.4 M	0.8 M	0.3 M	0.3 M	320 mm (wide), 1,500 mm (Tele)	0.3 M
IR LED Number	10 pcs	10 pcs	10 pcs	10 pcs	10 pcs	10 pcs	-	14 pcs
IR LED effective distance	5 M @50 IRE	5 M @50 IRE	10 M @50 IRE	10 M @50 IRE	16 M @50 IRE	16 M @50 IRE	-	30 M @50 IRE
Wide Dynamic Range	-	-	-	-	-	-	Yes	-
Back light compensation	Yes (BLC)	Yes (BLC)	Yes (BLC)	Yes (BLC)	Yes (BLC, on/off)	Yes (BLC, on/off)	Yes	Yes (BLC, on/off)
Noise Reduction	2DNR	2DNR	2DNR	2DNR	2DNR	2DNR	Yes	2DNR
Automatic tone reproduction	Yes (ATR-Lite)	Yes (ATR-Lite)	Yes (ATR-Lite)	Yes (ATR-Lite)	Yes (ATR-Lite, on/off)	Yes (ATR-Lite, on/off)	Yes	Yes (ATR-Lite, on/off)
OSD	-	-	-	-	-	-	-	-
User presets	-	-	-	-	-	-	-	-
RS485	-	-	-	-	-	-	-	-
GPIO In	-	-	-	-	-	-	-	-
GPIO Out	-	-	-	-	-	-	-	-
Back focus adjustment	-	-	-	-	-	-	-	-
Slow Shutter	-	-	-	-	-	-	-	-
Privacy Masking	-	-	-	-	-	-	-	-
Operating temperature	-10 °C to +50 °C	-10 °C to +50 °C	-10 °C to +50 °C	-10 °C to +50 °C	-10 °C to +50 °C	-10 °C to +50 °C	-10 °C to +50 °C	-10 °C to +50 °C
Storage temperature	-40 °C to +60 °C	-40 °C to +60 °C	-40 °C to +60 °C	-40 °C to +60 °C	-40 °C to +60 °C	-40 °C to +60 °C	-20 °C to +60 °C	-40 °C to +60 °C
Operating humidity	20 % to 80 %	20 % to 80 %	20 % to 80 %	20 % to 80 %	20 % to 80 %	20 % to 80 %	20 % to 80 %	20 % to 80 %
Storage humidity	20 % to 95 %	20 % to 95 %	20 % to 95 %	20 % to 95 %	20 % to 95 %	20 % to 95 %	20 % to 95 %	20 % to 95 %
Power requirement	DC12 V±10 %	DC12 V±10 %	DC12 V±10 %	DC12 V±10 %	AC24 V±10 %, DC12 V±10 %	AC24 V±10 %, DC12 V±10 %	AC24 V±10 %	AC24 V±10 %, DC12 V±10 %
Power consumption	Max 2.7 W	Max 2.7 W	Max 2.9 W	Max 2.9 W	Max 4.2 W	Max 4.2 W	Max 19 W	Max 5.5 W
Mass	280 g	280 g	280 g	280 g	280 g	320 g	1.7 kg (including ceiling bracket)	900 g
Dimensions	121.6 mm x 86.5 mm (Ø x H)	121.6 mm x 86.5 mm (Ø x H)	121.6 mm x 86.5 mm (Ø x H)	121.6 mm x 86.5 mm (Ø x H)	121.6 mm x 86.5 mm (Ø x H)	121.6 mm x 86.5 mm (Ø x H)	147.4 mm x 190.9 mm (Ø x H)	139.4 mm x 103 mm (Ø x H)
Supplied accessories	Template (1), Operation instructions (1)	Template (1), Operation instructions (1)	Template (1), Operation instructions (1)	Template (1), Operation instructions (1)	Template (1), Operation instructions (1)	Template (1), Operation instructions (1)	Ceiling bracket (1), Operating Instructions (1), Screw (2), Template (1), 24V AC connector (1), I/O connector (1)	Bracket (1), Template (1), Fall-prevention rope (1), Camera unit mounting screw (2), screw M4x8 (1), Wrench (1), Installation manual (1)

# Video Security Analogue Line-up 2012



© 2012 Sony Corporation. All rights reserved. Reproduction in whole or in part without permission is prohibited. Features and specifications are subject to change without notice. All non-metric weights and measurements are approximate. Sony is a trademark of Sony Corporation. HDMI and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. All other trademarks are the property of their respective owners.

**About Sony PSE**  
Sony PSE is the leading supplier of AV/IT solutions to businesses across a wide variety of sectors including **Media and Broadcast, Video Security and Retail, Transport & Large Venue markets**. It delivers products, systems and applications to enable the creation, manipulation and distribution of digital audio-visual content that add value to businesses and their customers. With over 25 years' experience in delivering innovative market-leading products, Sony PSE is ideally placed to deliver exceptional quality and value to its customers. Sony's PSE division, its systems integration arm, offers its customers access to the expertise and local knowledge of skilled professionals across Europe. Collaborating with a network of established technology partners, Sony PSE delivers end-to-end solutions that address the customer's needs, integrating software and systems to achieve each organisation's individual business goals. For more information please visit [www.pro.sony.eu](http://www.pro.sony.eu)



Model	Indoor Mini Dome									
	WIDE DYNAMIC					FIX DOME				
	SSC-FM531	SSC-FM561	SSC-N11	SSC-N12	SSC-N13	SSC-N14	SSC-N20	SSC-N21	SSC-N22	SSC-N24
Image device	1/3" Super HAD CCD II	1/3" Super HAD CCD II	1/3" 760H Super HAD CCD II	1/3" 760H Super HAD CCD II	1/3" 960H Exview HAD CCD II	1/3" 960H Exview HAD CCD II	1/3" 760H Super HAD CCD II	1/3" 960H Exview HAD CCD II	1/3" 760H Super HAD CCD II	1/3" 960H Exview HAD CCD II
Day/Night	Electrical D/N	Optical D/N	Electrical D/N	Electrical D/N	Electrical D/N	Electrical D/N	Electrical D/N	Electrical D/N	Optical D/N	Optical D/N
Number of effective pixels	Approx. 570,000 pixels (976 (H) x 582 (V))	Approx. 570,000 pixels (976 (H) x 582 (V))	Approx. 440,000 pixels (752 (H) x 582 (V))	Approx. 440,000 pixels (752 (H) x 582 (V))	Approx. 570,000 pixels (976 (H) x 582 (V))	Approx. 570,000 pixels (976 (H) x 582 (V))	Approx. 440,000 pixels (752 (H) x 582 (V))	Approx. 570,000 pixels (976 (H) x 582 (V))	Approx. 440,000 pixels (752 (H) x 582 (V))	Approx. 570,000 pixels (976 (H) x 582 (V))
Horizontal resolution	700 TVL	700 TVL	540 TVL	540 TVL	650 TVL	650 TVL	540 TVL	650 TVL	540 TVL	650 TVL
Vandal Resistant Ingress Protection	-	-	-	-	-	-	-	-	-	-
Minimum Illumination Color	50 IRE 0.1 lx	0.1 lx	0.55 lx	0.30 lx	0.40 lx	0.30 lx	0.15 lx	0.15 lx	0.15 lx	0.15 lx
Minimum Illumination B/W	30 IRE 0.06 lx	0.06 lx	0.35 lx	0.18 lx	0.20 lx	0.18 lx	0.08 lx	0.08 lx	0.08 lx	0.08 lx
Minimum Illumination Condition	F1.2, 50 IRE, AGC ON, Turbo mode	F1.2, 50 IRE, AGC ON, Turbo mode	F2.0 AGC ON	F1.8 AGC ON	F2.0 AGC ON	F1.8 AGC ON	F1.2 AGC ON	F1.2 AGC ON	F1.2 AGC ON	F1.2 AGC ON
Signal system	PAL	PAL	PAL	Pal	PAL	PAL	PAL	PAL	PAL	PAL
Video output	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p
S/N ratio	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)
Synchronization	Internal/AC line lock selectable	Internal/AC line lock selectable	Internal Only	Internal Only	Internal Only	Internal Only	Internal/AC line lock selectable	Internal/AC line lock selectable	Internal/AC line lock selectable	Internal/AC line lock selectable
Gain control	OFF/Normal/Turbo/Manual	OFF/Normal/Turbo/Manual	Auto (on/off)	Internal Only	Internal Only	Internal Only	Auto (on/off)	Auto (on/off)	Auto (on/off)	Auto (on/off)
Shutter Speed	1/50 to 1/100,000 (12 steps), OFF/MANUAL/CCD-IRIS selectable	1/50 to 1/100,000 (12 steps), OFF/MANUAL/CCD-IRIS selectable	Auto	Auto	Auto	Auto	Fixed (1/50 s)	Fixed (1/50 s)	Fixed (1/50 s)	Fixed (1/50 s)
White balance	ATW/ATW-PRO/3200K/5600K/Manual	ATW/ATW-PRO/3200K/5600K/Manual	ATW (2000K-10000K)	ATW (2000K-10000K)	ATW (2000K-10000K)	ATW (2000K-10000K)	ATW (2000K-10000K), ATW-pro (2500K-6000K)	ATW (2000K-10000K), ATW-pro (2500K-6000K)	ATW (2000K-10000K), ATW-pro (2500K-6000K)	ATW (2000K-10000K), ATW-pro (2500K-6000K)
Lens type	Varifocal type	Varifocal type	Mono-focal type	Mono-focal type	Mono-focal type	Mono-focal type	Varifocal type	Varifocal type	Varifocal type	Varifocal type
Lens Mount	-	-	-	-	-	-	-	-	-	-
Focal Length	f = 2.8 to 10.5 mm	f = 2.8 to 10.5 mm	f = 3.0 mm	f = 6.0 mm	f = 3.0 mm	f = 6.0 mm	f = 2.8 to 10.5 mm	f = 2.8 to 10.5 mm	f = 2.8 to 10.5 mm	f = 2.8 to 10.5 mm
Zoom Ratio	Optical 3.7 x	Optical 3.7 x	-	Optical 3.7 x	Optical 3.7 x	Optical 3.7 x	Optical 3.7 x	Optical 3.7 x	Optical 3.7 x	Optical 3.7 x
F number	F1.2 (Wide), F2.6 (Tele)	F1.2 (Wide), F2.6 (Tele)	F2.0	F1.8	F2.0	F1.8	F1.2 (Wide), F2.6 (Tele)	F1.2 (Wide), F2.6 (Tele)	F1.2 (Wide), F2.6 (Tele)	Optical 3.7 x
Angle of View (H)	99.5 to 27.4 degree	101.8 to 27.4 degree	95.9 degree	46 degree	95.9 degree	46 degree	99.5 to 27.4 degree	99.5 to 27.4 degree	101.8 to 27.4 degree	101.8 to 27.4 degree
Panning range	355 degree	355 degree	340 degree	340 degree	340 degree	340 degree	355 degree	355 degree	355 degree	355 degree
Tilting range	±77 degree	±77 degree	±45.3 degree	±75 degree	±75 degree	±75 degree	±77 degree	±77 degree	±77 degree	±77 degree
Swivel range	350 degree	350 degree	340 degree	340 degree	340 degree	340 degree	350 degree	350 degree	350 degree	350 degree
Minimum object distance	0.3 M	0.3 M	0.4 M	0.4 M	0.4 M	0.4 M	0.3 M	0.3 M	0.3 M	0.3 M
IR LED Number	-	-	-	-	-	-	-	-	-	-
IR LED effective distance	-	-	-	-	-	-	-	-	-	-
Wide Dynamic Range	75 dB typical	75 dB typical	-	-	-	-	-	-	-	-
Back light compensation	OFF/DynaViewSX/IBLC/SPOT	OFF/DynaViewSX/IBLC/SPOT	Yes (BLC, on/off)	Yes (BLC, on/off)	Yes (BLC, on/off)	Yes (BLC, on/off)	Yes (BLC, on/off)	Yes (BLC, on/off)	Yes (BLC, on/off)	Yes (BLC, on/off)
Noise Reduction	Yes (2D/3DNR, Weak/Normal/Strong)	Yes (2D/3DNR, Weak/Normal/Strong)	Yes (2DNR, on/off)	Yes (2DNR, on/off)	Yes (2DNR, on/off)	Yes (2DNR, on/off)	Yes (2DNR, on/off)	Yes (2DNR, on/off)	Yes (2DNR, on/off)	Yes (2DNR, on/off)
Automatic tone reproduction	Yes (DynaViewSX mode only)	Yes (DynaViewSX mode only)	Yes (ATR-Lite, on/off)	Yes (ATR-Lite, on/off)	Yes (ATR-Lite, on/off)	Yes (ATR-Lite, on/off)	Yes (ATR-Lite, on/off)	Yes (ATR-Lite, on/off)	Yes (ATR-Lite, on/off)	Yes (ATR-Lite, on/off)
OSD	Yes	Yes	-	-	-	-	-	-	-	-
User presets	A/B Preset selectable	A/B Preset selectable	-	-	-	-	-	-	-	-
RS485	-	-	-	-	-	-	-	-	-	-
GPIO In	-	x1 (Day/Night Control)	-	-	-	-	-	-	-	-
GPIO Out	-	x1 (Day/Night Control)	-	-	-	-	-	-	-	-
Back focus adjustment	-	-	-	-	-	-	-	-	-	-
Slow Shutter	OFF/x2/x4/x8/x16/x32/x64/x128/x256/x512	OFF/x2/x4/x8/x16/x32/x64/x128/x256/x512	-	-	-	-	-	-	-	-
Privacy Masking	ON/OFF selectable (with area setting function)	ON/OFF selectable (with area setting function)	-	-	-	-	-	-	-	-
Operating Temperature	-10 °C to +50 °C	-10 °C to +50 °C	-10 °C to +50 °C	-10 °C to +50 °C	-10 °C to +50 °C	-10 °C to +50 °C	-10 °C to +50 °C	-10 °C to +50 °C	-10 °C to +50 °C	-10 °C to +50 °C
Storage Temperature	-40 °C to +60 °C	-40 °C to +60 °C	-40 °C to +60 °C	-40 °C to +60 °C	-40 °C to +60 °C	-40 °C to +60 °C	-40 °C to +60 °C	-40 °C to +60 °C	-40 °C to +60 °C	-40 °C to +60 °C
Operating humidity	20 % to 80 %	20 % to 80 %	20 % to 80 %	20 % to 80 %	20 % to 80 %	20 % to 80 %	20 % to 80 %	20 % to 80 %	20 % to 80 %	20 % to 80 %
Storage humidity	20 % to 95 %	20 % to 95 %	20 % to 95 %	20 % to 95 %	20 % to 95 %	20 % to 95 %	20 % to 95 %	20 % to 95 %	20 % to 95 %	20 % to 95 %
Power requirement	AC24 Va10%, DC12 Va10%	AC24 Va10%, DC12 Va10%	DC12V ±10%	DC12V ±10%	DC12V ±10%	DC12V ±10%	AC24 Va10%, DC12 Va10%	AC24 Va10%, DC12 Va10%	AC24 Va10%, DC12 Va10%	AC24 Va10%, DC12 Va10%
Power consumption	Max 2.8 W	Max 2.8 W	Max 0.9 W	Max 0.9 W	Max 0.9 W	Max 0.9 W	Max 1.5 W	Max 1.5 W	Max 1.7 W	Max 1.7 W
Mass	320 g	330 g	125 g	140 g	125 g	140 g	320 g	320 g	320 g	320 g
Dimensions	Ø 121.6 mm x 86.5 mm	Ø 121.6 mm x 86.5 mm	84 mm x 63 mm (Ø x H)	85.2 mm x 63.5 mm (Ø x H)	84 mm x 63 mm (Ø x H)	85.2 mm x 63.5 mm (Ø x H)	121.6 mm x 86.5 mm (Ø x H)	121.6 mm x 86.5 mm (Ø x H)	121.6 mm x 86.5 mm (Ø x H)	121.6 mm x 86.5 mm (Ø x H)
Supplied accessories	Operating instructions x1, Menu Instructions x1, Template x1	Operating instructions x1, Menu Instructions x1, Template x1	Operating instructions x1	Operating instructions x1	Operating instructions x1	Operating instructions x1	Operating instructions x1, Template x1	Operating instructions x1, Template x1	Operating instructions x1, Template x1	Operating instructions x1, Template x1

Model	Indoor Box																IR BOX				IR BULLET		Outdoor Box								
	BOX																SSC-YB401R		SSC-YB411R		SSC-YB501R		SSC-YB511R		SSC-CB461R		SSC-CB561R		SSC-CB565R		SSC-CB575R
	SSC-FB531	SSC-FB561	SSC-G103	SSC-G203	SSC-G113	SSC-G213	SSC-G108	SSC-G208	SSC-G118	SSC-G218	SSC-G813	SSC-G818	SSC-YB401R	SSC-YB411R	SSC-YB501R	SSC-YB511R	SSC-CB461R	SSC-CB561R	SSC-CB565R	SSC-CB575R											
Image device	1/3-type Super HAD CCD II	1/3-type Super HAD CCD II	1/3" 760H Super HAD CCD II	1/3" 760H Super HAD CCD II	1/3" 960H Exview HAD CCD II	1/3" 960H Exview HAD CCD II	1/3" 760H Super HAD CCD II	1/3" 960H Exview HAD CCD II	1/3" 760H Super HAD CCD II	1/3" 960H Exview HAD CCD II	1/2" 760H Exwave-HAD-Technology	1/2" 760H Exwave-HAD-Technology	1/3" 760H Super HAD CCD II	1/3" 760H Super HAD CCD II	1/3" 960H Exview HAD CCD II	1/3" 960H Exview HAD CCD II	1/3" 760H Super HAD CCD II	1/3" 960H Exview HAD CCD II	1/3" 960H Exview HAD CCD II	1/3" 960H Exview HAD CCD II											
Day/Night	Electrical D/N	Optical D/N	Electrical D/N	Optical D/N	Electrical D/N	Optical D/N	Electrical D/N	Optical D/N	Electrical D/N	Optical D/N	Optical D/N	Optical D/N	Electrical D/N	Electrical D/N	Optical D/N	Optical D/N	Optical D/N	Optical D/N	Optical D/N	Optical D/N											
Number of effective pixels	Approx. 570,000 pixels (976 (H) x 582 (V))	Approx. 570,000 pixels (976 (H) x 582 (V))	Approx. 570,000 pixels (976 (H) x 582 (V))	Approx. 440,000 pixels (752 (H) x 582 (V))	Approx. 570,000 pixels (976 (H) x 582 (V))	Approx. 570,000 pixels (976 (H) x 582 (V))	Approx. 440,000 pixels (752 (H) x 582 (V))	Approx. 570,000 pixels (976 (H) x 582 (V))	Approx. 440,000 pixels (752 (H) x 582 (V))	Approx. 570,000 pixels (976 (H) x 582 (V))	Approx. 440,000 pixels (752 (H) x 582 (V))	Approx. 440,000 pixels (752 (H) x 582 (V))	Approx. 440,000 pixels (752 (H) x 582 (V))	Approx. 440,000 pixels (752 (H) x 582 (V))	Approx. 570,000 pixels (976 (H) x 582 (V))	Approx. 570,000 pixels (976 (H) x 582 (V))	Approx. 440,000 pixels (752 (H) x 582 (V))	Approx. 570,000 pixels (976 (H) x 582 (V))	Approx. 570,000 pixels (976 (H) x 582 (V))	Approx. 570,000 pixels (976 (H) x 582 (V))											
Horizontal resolution	700 TVL (Sharp mode)	700 TVL (Sharp mode)	540 TVL	540 TVL	650 TVL	650 TVL	540 TVL	540 TVL	650 TVL	650 TVL	540 TVL	540 TVL	540 TVL	540 TVL	650 TVL	650 TVL	540 TVL	700 TVL (Sharp mode) 650 TVL (Normal mode)	700 TVL (Sharp mode) 650 TVL (Normal mode)	700 TVL (Sharp mode) 650 TVL (Normal mode)											
Vandal Resistant Ingress Protection	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											
Minimum Illumination Color	0.08 lx	0.08 lx	0.15 lx	0.15 lx	0.15 lx	0.15 lx	0.15 lx	0.15 lx	0.15 lx	0.15 lx	0.28 lx	0.28 lx	0.06 lx	0.06 lx	0.06 lx	0.06 lx	0.06 lx	0.06 lx	0.06 lx	0.06 lx											
Minimum Illumination B/W	0.05 lx	0.05 lx	0.08 lx	0.08 lx	0.08 lx	0.08 lx	0.08 lx	0.08 lx	0.08 lx	0.08 lx	0.15 lx	0.15 lx	0.04 lx	0.04 lx	0.04 lx	0.04 lx	0.04 lx	0.04 lx	0.04 lx	0.04 lx											
Minimum Illumination Condition	F1.2, 50IRE, AGC ON, Turbo mode	F1.2, 50IRE, AGC ON, Turbo mode	F1.2 AGC ON	F1.2 AGC ON	F1.2 AGC ON	F1.2 AGC ON	F1.2 AGC ON	F1.2 AGC ON	F1.2 AGC ON	F1.2 AGC ON	F1.2 AGC ON	F1.2 AGC ON	F2.0 AGC ON	F1.8 AGC ON	F2.0 AGC ON	F1.8 AGC ON	F1.2 AGC ON	F1.2 AGC ON	F1.2 AGC ON	F1.2 AGC ON											
Signal system	PAL	PAL	PAL	PAL	PAL	PAL	PAL	PAL	PAL	PAL	PAL	PAL	PAL	PAL	PAL	PAL	PAL	PAL	PAL	PAL											
Video output	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p	VBS1.0Vp-p											
S/N ratio	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)	More than 57 dB (AGC Off)	More than 57 dB (AGC Off)	More than 55 dB	More than 55 dB	More than 55 dB	More than 55 dB	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)	More than 55 dB (AGC Off)											
Synchronization	Internal/AC line lock selectable	Internal/AC line lock selectable	Internal/AC line lock selectable	Internal/AC line lock selectable	Internal/AC line lock selectable	Internal/AC line lock selectable	Internal/AC line lock selectable	Internal/AC line lock selectable	Internal/AC line lock selectable	Internal/AC line lock selectable	Internal/AC line lock selectable	Internal/AC line lock selectable	Internal Only	Internal Only	Internal Only	Internal Only	Internal/AC line lock selectable	Internal/AC line lock selectable	Internal/AC line lock selectable	Internal/AC line lock selectable											
Gain control	OFF/Normal/Turbo/Manual	OFF/Normal/Turbo/Manual	Auto (on/off)	Auto (on/off)	Auto (on/off)	Auto (on/off)	Auto (on/off)	Auto (on/off)	Auto (on/off)	Auto (on/off)	Auto (on/off)	Auto (on/off)	Auto	Auto	Auto	Auto	Auto (on/off)	Auto (on/off)	Auto (on/off)	Auto (on/off)											
Shutter Speed	1/50 to 1/100,000 (12 steps), OFF/MANUAL/CCD-IRIS selectable	1/50 to 1/100,000 (12 steps), OFF/MANUAL/CCD-IRIS selectable	Fixed (1/50 s, Default), Auto or 8 Fixed steps Selectable	Fixed (1/50 s, Default), Auto or 8 Fixed steps Selectable	Fixed (1/50 s, Default), Auto or 8 Fixed steps Selectable	Fixed (1/50 s, Default), Auto or 8 Fixed steps Selectable	Fixed (1/50 s, Default), Auto or 8 Fixed steps Selectable	Fixed (1/50 s, Default), Auto or 8 Fixed steps Selectable	Fixed (1/50 s, Default), Auto or 8 Fixed steps Selectable	Fixed (1/50 s, Default), Auto or 8 Fixed steps Selectable	1/50 to 1/100,000 (12steps) Off / Manual / CCD-IRIS selectable	1/50 to 1/100,000 (12steps) Off / Manual / CCD-IRIS selectable	Auto	Auto	Auto	Auto	Fixed (1/50 s)	Fixed (1/50 s)	Fixed (1/50 s)	Fixed (1/50 s)											
White balance	ATW/ATW-PRO/3200K/5600K/Manual	ATW/ATW-PRO/3200K/5600K/Manual	ATW (2000K-10000K), ATW-pro (2500K-6000K)	ATW (2000K-10000K), ATW-pro (2500K-6000K)	ATW (2000K-10000K), ATW-pro (2500K-6000K)	ATW (2000K-10000K), ATW-pro (2500K-6000K)	ATW (2000K-10000K), ATW-pro (2500K-6000K)	ATW (2000K-10000K), ATW-pro (2500K-6000K)	ATW (2000K-10000K), ATW-pro (2500K-6000K)	ATW (2000K-10000K), ATW-pro (2500K-6000K)	ATW/ATW-PRO/3200K/5600K/Manual	ATW/ATW-PRO/3200K/5600K/Manual	ATW (2000K-10000K)	ATW (2000K-10000K)	ATW (2000K-10000K)	ATW (2000K-10000K)	ATW (2000K-10000K), ATW-pro (2500K-6000K)	ATW (2000K-10000K), ATW-pro (2500K-6000K)	ATW (2000K-10000K), ATW-pro (2500K-6000K)	ATW (2000K-10000K), ATW-pro (2500K-6000K)											
Lens type	-	-	-	-	-	-	-	-	-	-	-	-	Mono-focal type	Mono-focal type	Mono-focal type	Mono-focal type	Varifocal type	Varifocal type	Varifocal type	Varifocal type											
Lens Mount	CS Mount	CS Mount	CS Mount																												