

TeleEye NX301 Video Server – Professional Solutions for IP & Mobile Surveillance Applications



Brand	TeleEye
Model Code	NX301 Single Channel Video Server
Audio Input / Output	1 Channel, RCA, Line Level
Audio Bit Rate	7.2 / 32kbps
Video Refreshing Frame Rate	25 / 30 fps at D1 Resolution
RS485 Output	Yes
Network Interface	Ethernet (RJ-45 Wired, 10 / 100 Base-T)
Network Protocol	TCP / IP, DHCP, HTTP, SNTP, DDNS, DNS, SMTP
Concurrent Users	6
Web Server	Built-in
USB Interface	USB 2.0, 480Mbps
Compression	SMAC-M Multi-stream
Event	External Alarm, Motion Detection, Video Loss
Action	Dial Back, E-mail, Relay Switch
Alarm Input / Relay Output	1
Power Rating	DC 12V, 12W (max.)
Power Out	Yes (12V DC, 500mA)
Physical Specifications	Dimensions (mm): 164 x 88 x 50 Weight (kg): 0.45

Model Info

Mobile Surveillance:

1. Support video monitoring on mobile phone.
2. Support 3G Modem for video transmission on HSDPA, UMTS, & GPRS mobile network.

NX301 comes with:

1. *sureLINK* Technology: Obtain real time video on Internet by a dynamic IP address.
2. Power over Ethernet (PoE): Data and power supplying on a single CAT5 cable. Fully IEEE 802.3af compliant.