



Scan the QR code or link to the address below to find a list of datasheets to all products and other support information.

<https://www.tm-readers.com/downloads.htm>



Overview

Having a larger footprint, the RX3 can be fixed to a UK or EU electrical back box, or a standard single gang US back box. The larger profile offers an easily recognisable access point location. As most of the RXseries® this powerfully secure reader supports a wide variety of output formats, allowing it to be used in most access control systems.

The combination of an integral speaker, RGB LED and audible buzzer provides a flexible platform to give the right user interface configuration for your project.



Mechanical

Dimensions	120 x 876 x 21 mm (4.7 x 3.0 x 0.8 inches)
Housing	Moulded polycarbonate
Mounting	Suitable plain surface
Fixing	4mm., max' diameter + UK/EU/US electrical back box

Environmental

Operating temp'	-35°C to +66°C
Humidity	85±5% at 30±2°C (86±3°F)
Ingress	IP67
Impact	IK10
Flammability	UL94V-0

Electrical


Voltage	see table below
Current	see table below
Data Voltage	Rest >4Vdc / Active <1Vdc
Data output	see table below
Indication	1 RGB LED
Sounder	Integral speaker
Termination	screw terminal connection block

Reader Models are sold as customer-specific configurations.

Please call +44 (0) 1495 751 992 to discuss your custom configuration or LEGIC® reader requirements.

READER MODEL	Frequency	Current mA	Voltage Vdc	Technology	Optical tamper	Wiegand Clock & Data	Bluetooth®	OSDP	FCC	UL294
RX300	125 kHz	115	5 - 12	125kHz EM variants		•				
RX380PLUS	13.56 MHz 125 kHz	200	5 - 12	MIFARE® Sector + 125kHz		•				
RX360	13.56 MHz 125 kHz 2.4 GHz ○	75	10 - 16	LEGIC® + ECP 2.0 + 125kHz	•	•	○	○	•	•
RX390	13.56 MHz 125 kHz 2.4 GHz ○	75	10 - 16	MIFARE®DESFire® + ECP 2.0 + 125kHz	•	•	○	○	•	•

○ - optional



The RX3 boasts multiple technologies embedded in its hardware and firmware, including an Apple Certified ECP 2.0 integration for Apple Access passes (in select variants).

Also included is a 13.56MHz MIFARE®DESFire® platform, having state-of-the-art security and privacy along with the full complement of LEGIC® 13.56MHz contactless smart technology, with its tightly integrated LEGIC RF Standard. In addition, the reader can also be used for 125kHz access control systems, including other widely used 125kHz technologies such as:

- KANTECH
- FARPOINTE
- AWID
- CASI
- EM variants

Key features

- Multi-technology
- UK design and manufacture
- Black high gloss finish
- Slim profile
- RGB LED
- Fully encapsulated electronics
- Optical tamper switch (see table above)
- Wide range of output formats
- Read range up to 10cm (4 inches)
- 5 year limited warranty



All copyrights © and trademarks ® / ™ are acknowledged and remain the property of their respective owners.
 NOTE: certifications not available to all reader models.

The Bluetooth word, mark and logo are registered trademarks of Bluetooth SIG, Inc. 'MIFARE', 'MIFARE Classic' and 'MIFARE DESFire' are trademarks of NXP B.V.

RXSERIES® © Third Millennium Systems Ltd
 registered in England & Wales No. 31199053

Third Millennium Systems Ltd.
 18 / 19 Torfaen Business Centre
 Panteg Way New Inn PONTYPOOL NP4 0LS United Kingdom

100-03062-RX3-G E&OE SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

tel: +44 (0) 1495 751 992 web: www.tm-readers.com contact: info@tm-readers.com