


DVR 42

960H H.264 Digital Video Recorder



OVERVIEW

The TruVision® DVR 42 (TVR 42) is a cost-effective, full-size digital video recorder with 8 or 16-channel capabilities. It utilizes H.264 video compression technology to deliver real-time recording per channel at an outstanding 960H resolution.

A built-in Web browser and access through mobile apps allows you to stay connected remotely via any Web-enabled device. Login via smartphone or tablet to configure, view, search, play back, archive and monitor facilities, people or valuables. Compatible with TruVision Navigator, the DVR 42 integrates easily with existing systems and features a familiar, user-friendly interface. Start-up Wizards make installation and DDNS setup quick and simple.

With an internal redundant storage feature, up to 12TB of mirrored data is stored on 6 HDDs so video recordings are never lost, even in event of HDD failure. Video can also be archived via CD, DVD, USB memory stick, NAS and eSATA devices. For user-friendly, remote management and reliable, real-time recording, the DVR 42 represents a comprehensive solution to fit your needs and budget.

STANDARD FEATURES

- Built-in CD/DVD burner
- H.264 compression technology
- 8 or 16-channel real-time recording at 960H resolution
- Mobile apps allow you to connect remotely via smartphone or tablet to keep an eye on facilities, people or valuables
- Redundant storage protects data in event of HDD failure
- Remote management allows you to configure, view, search, play back, archive and monitor health
- Set-up Wizards for quick and easy installation, search and playback
- PTZ and dome camera control via mouse, front panel joystick and IR remote control
- E-mail notification upon alarm with attached images
- Multiple output monitor support (HDMI, VGA, Analog, Spot)
- Fully compatible with TruVision Navigator software
- Integrates easily with existing systems
- Familiar, user-friendly interface
- Camera to HDD assignment for HDD data grouping
- Features up to 12TB internal storage
- Time lapse, event and alarm recording settings
- HDMI or VGA outputs for high-quality local viewing
- Sub-stream recording and playback for low bandwidth situations

DVR 42

960H H.264 Digital Video Recorder


North America
T 855-286-8889

Latin America
T 561-998-6114

Specifications

Model	TVR4208	TVR4216	
Video/Audio Input	Video Compression	H.264	
	Analog Video Input	8-channel, BNC, (1.0 Vp-p, 75 Ω), PAL/NTSC self-adaptive	16-channel, BNC, (1.0 Vp-p, 75 Ω), PAL/NTSC self-adaptive
	Audio Compression	Ogg Vorbis	
	Audio Input	8-channel, RCA, (2.0 Vp-p, 1 Ω)	16-channel, RCA, (2.0 Vp-p, 1 Ω)
	Two-Way Audio	1-channel, RCA (2.0 Vp-p, 1Ωk)	
Video/Audio Output	HDMI Output	1-channel, resolution: 1920x1080P/60Hz, 1920x1080P/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	
	VGA Output	1-channel, resolution: 1920x1080P/60Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	
	Analog Output	1-channel, BNC, (1.0 Vp-p, 75 Ω)	
	Video Spot Output	1-channel, BNC, (1.0 Vp-p, 75 Ω)	
	Video Loop Out	8-channel	16-channel
	Encoding Resolution	960H/4CIF/2CIF/CIF/QCIF	
	Frame Rate	25 fps (PAL)/30 fps (NTSC)	
	Video Bit Rate	32Kbps-4096Kbps, or user-defined (Max. 4096Kbps)	
	Audio Output	2-channel, RCA (Linear, 600 Ω)	
	Audio Bit Rate	16Kbps	
	Dual-Stream	Sub-stream at CIF/QCIF: 25 fps (PAL)/30 fps (NTSC)	
	Stream Type	Video, Video & Audio	
	Playback Resolution	960H/4CIF/2CIF/CIF/QCIF	
	Synchronous Playback	8-channel	16-channel
Hard Disk	SATA	(8) SATA interfaces (internal)	
	eSATA	(1) eSATA interface	
	Capacity	Up to 2TB capacity for each disk	
External Interface	Network Interface	(1) RJ45 10M/100M/1000M Ethernet Interface	
	Serial Interface	(1) RS-232 Interface (for Probridge, Challenger, Technical Support); (1) RS-485 interface (for PTZ control); (1) RS-485 keyboard interface (for KTD405 keyboard control)	
	USB Interface	(2) USB 2.0	
	Alarm In	16	
	Alarm Out	4	
General	Power	100~240VAC, 6.3A, 50~60Hz	
	Consumption (without hard disk or DVD-R/W)	≤ 40 W	≤ 45 W
	Working Temperature	14°F~131°F (-10°C~55°C)	
	Working Humidity	10%~90%	
	Chassis	2U	
	Dimensions (W x D x H)	17.52 x 18.5 x 3.54 in. (445 x 470 x 90mm)	
	Weight	≤ 8 kg (without hard disk or DVD-R/W)	
	Rack Mount	Included	

Dimensional Diagram



Ordering Information

TVR-4208-2T	TruVision DVR 42, 960H H.264, 8-Channels, DVD/CD, 2TB Storage
TVR-4208-4T	TruVision DVR 42, 960H H.264, 8-Channels, DVD/CD, 4TB Storage
TVR-4216-2T	TruVision DVR 42, 960H H.264, 16-Channels, DVD/CD, 2TB Storage
TVR-4216-4T	TruVision DVR 42, 960H H.264, 16-Channels, DVD/CD, 4TB Storage
TVR-4216-8T	TruVision DVR 42, 960H H.264, 16-Channels, DVD/CD, 8TB Storage
TVR-4216-12T	TruVision DVR 42, 960H H.264, 16-Channels, DVD/CD, 12TB Storage

TruVision® DVR 42 Storage Tables

16-Channel Models

Storage	30 Days			60 Days			90 Days		
	2CIF	4CIF	960H	2CIF	4CIF	960H	2CIF	4CIF	960H
2TB HDD	12 fps	6 fps	4 fps	4 fps	2 fps	2 fps	2 fps	1 fps	1 fps
4TB HDD	30 fps	16 fps	15 fps	12 fps	6 fps	4 fps	6 fps	2 fps	1 fps
8TB HDD	30 fps	30 fps	30 fps	30 fps	15 fps	15 fps	18 fps	10 fps	8 fps
12TB HDD	30 fps	30 fps	30 fps	30 fps	30 fps	22 fps	30 fps	18 fps	16 fps

8-Channel Models

Storage	30 Days			60 Days			90 Days		
	2CIF	4CIF	960H	2CIF	4CIF	960H	2CIF	4CIF	960H
2TB HDD	20 fps	10 fps	8 fps	8 fps	4 fps	4 fps	8 fps	2 fps	2 fps
4TB HDD	30 fps	22 fps	22 fps	30 fps	16 fps	16 fps	18 fps	10 fps	10 fps
8TB HDD	30 fps	30 fps	30 fps	30 fps	30 fps	30 fps	30 fps	22 fps	22 fps



interlogix.com

Specifications subject to change without notice.

© 2014 United Technologies Corporation.

All rights reserved.

Interlogix is part of UTC Building and Industrial Systems, a unit of United Technologies Corporation.

402-3792 2014/02 (76900)