



**0911\*), 0911-P\*)**

Access Control

## **Active Cotag keyring tag**

---

The **0911/0911-P** is an active tag that includes a lithium battery which enables it to provide hands-free functionality when it is used together with Cotag hands-free readers. For example, the combination of the 0911/0911-P tag and the HF500 reader results in a reading range of approximately 85 cm. The reading range when the 0911/0911-P is used in combination with Cotag proximity readers varies from approximately 9 to 25 cm. 0911/0911-P tags are particularly useful in environments where some cardholders are disabled or often have their hands full (i.e. a hospital or warehouse)

One of the major advantages of Cotag technology is that active and passive cards can be mixed in the same system to provide ultimate convenience and cost-efficiency.

\*) The **0911** is a tag without any numbers encoded. Customer needs to program the complete number segment.

The **0911-P** is a 0911 tag which is encoded according to customer specification.

## Technical data

---

### 0911, 0911-P

---

Dimensions (W x H x D)	31.24 x 49.89 x 9.7 mm
------------------------	------------------------

---

## Details for ordering

---

Type	Part no	Designation
0911	GBI:51-600	Active non-encoded Cotag keyring tag
0911-P	GBI:51-604	Active customized-encoded Cotag keyring tag. Minimum order quantity: 100 pcs

Issued by  
Siemens AB  
Security Products  
International Headquarters  
Englundavägen 7  
SE-171 24 Solna  
Tel. +46 8 629 0300

© 2011 Copyright by Siemens AB

Data and design subject to change without notice.  
Supply subject to availability.

[www.siemens.com/securityproducts](http://www.siemens.com/securityproducts)

---

Document no. **A6V10330060**

Edition 05.2011