



ADD5100, ADD5110, ADD5160, ADD5190

SiPass®
integrated

Dual Reader Interface (DRI)

-
- **Interface module for up to two card readers**
 - **Support for an entry reader and an exit reader to monitor and control a door from both sides**
 - **Easy installation**
 - **Four product variants in three different housings**

The ADD5100, ADD5110, ADD5160 and ADD5190 act as an interface between card readers and the advanced central controller (AC5100 or AC5200). Each of them can support up to two card readers. When a cardholder presents an access card at an entry or exit reader the dual reader interface interprets the encoded information and sends this data to the controller. The controller then checks the validity of the cardholder, and if the appropriate permissions have been assigned, the controller sends a message back to the dual reader interface allowing it to unlock the door and provide passage. A dual reader interface can also report the status of the door (locked or unlocked) at any time.

Features

- Supports all popular reader technologies
- Supports all readers with SiPass reader protocol
- Support for an entry reader and an exit reader
- Auxiliary 12VDC power source (min. voltage input 18VDC)
- Lock / door strike output (relay driven)
- Request-to-exit input
- Door contact input
- Three auxiliary inputs
- Auxiliary output (relay driven)
- Selectable supervision of input wires
- Communications status LED
- Activity status LED
- Power status LED
- Host system compatibility for configuration download via ACC

Description

ADD5100, ADD5110, ADD5160 and ADD5190 dual reader controllers (DRIs) secure doors or barriers by supporting one entry reader, one exit reader, a door strike to lock and unlock the door, and a door contact to detect the door's position (open or closed).

The on-board inputs of a DRI are individually supervised, which ensures that any wire tampering generates an alarm message in the system.

Each DRI has three programmable auxiliary input connections for the monitoring of system aspects such as cabinet doors, duress switches, or PIR motion sensors. A DRI also includes an auxiliary output which can be connected to a buzzer, strobe light or similar device and configured to trigger that device when security is breached.

The DRIs are fully updateable using the latest flash technology, and can be easily programmed via the host system to operate in their intended mode. This leading-edge technology allows the DRIs to be re-programmed or re-configured and used in conjunction with other Siemens security products, providing a complete and fully expandable security system.

The DRIs have been carefully engineered so that they can be easily mounted in a variety of environments. Most commonly a DRI is either installed near the door which it controls, or centrally in the same cabinet as the advanced central controller.


Housing options

The DRI is available in three different variants in addition to the basic module (DRI including base plate) shown on the first page of this data sheet.

ADD5110 – DRI including base plate and plastic housing



ADD5160 – DRI in weatherproof housing



ADD5190 – DRI in a cabinet



Technical data

ADD5100, ADD5110, ADD5160, ADD5190	
Interface	FLN connection to controller: RS485 To readers: One RS485 bus for up to two RS485 readers (CerPass protocol) OR two Wiegand/Clock&Data ports
Operating voltage	12 to 32 VDC ±20 %
Power output	Reader: 300 mA Ancillary: 1 A
Power consumption	25 W
Outputs	1 x Lock output relay (30 VDC, 2 A) 1 x Auxiliary relay (30 VDC, 2 A)
Inputs	1 x REX button 1 x Door contact 3 x Auxiliary All inputs unsupervised or supervised
Tamper switch	Optional, auxiliary input
Firmware	Flash upgradeable
Indicators	Power, Activity, Communication
Operating temperature	0 to +50 °C
IP rating	ADD5110: IP55 ADD5160: IP66 ADD5190: IP20
Housing	ADD5110: ABS plastic ADD5160: ABS plastic ADD5190: Steel
Dimensions (W x H x D)	ADD5100: 125 x 125 x 34 mm ADD5110: 150 x 150 x 76 mm ADD5160: 180 x 180 x 60 mm ADD5190: 200 x 300 x 95 mm
Approval	ADD5100: CE, UL294, C-Tick ADD5110: CE ADD5160: CE ADD5190: CE

Details for ordering

Type	Part no.	Designation	Weight
ADD5100 ¹	6FL7820-8CA10	Dual reader interface including base plate	0.30 kg
ADD5110 ²	6FL7820-8CA11	Dual reader interface including base plate and plastic housing	0.55 kg
ADD5160	6FL7820-8CA16	Dual reader interface in weatherproof housing	0.50 kg
ADD5190	S54505-C16-A1	Dual reader interface in cabinet	2.8 kg

¹ Replaces type designation RIM-010

² Replaces type designation RIM-011

Issued by
Siemens Building Technologies
Fire & Security Products GmbH & Co. oHG
D-76181 Karlsruhe
www.buildingtechnologies.siemens.com

© 2009 Copyright by
Siemens Building Technologies
Fire & Security Products GmbH & Co. oHG
Data and design subject to change without notice.
Supply subject to availability.

Document no. **A24205-A335-B115**
Edition 03.12.2009