

Intrusion Detectors
 Internal Motion Detectors
 Wireless Detectors and Peripherals



Type

Order No.

ISRW6-12..

Wireless outdoor siren (compatible with IC60 and SI series)

The Intrunet outdoor siren communicates wirelessly thanks to an extension of the SiWay protocol named Si2Way. This communication protocol allows Si2Way components not only to send information to the control panel, but also to receive commands from the panel. The ISRW6-12.. comes with an embedded Si2Way radio module and powerful standard batteries ensuring a long maintenance cycles. The activation of the siren can be either time limited or disabled if required by the application. In addition to the powerful acoustic signal (100 dB at 1 m), an integrated light strobe flashes up siren activation.

Wireless protocol	Si2Way
Frequency	868 MHz
Wireless module range	Up to 300 m at open space
Sound level	Siren: 100 dB @ 1.00 m
Battery lifetime	3 years under normal conditions
Battery	ER34615M 3.6V, 14 Ah, D size
Housing protection (EN 60529)	IP54
Humidity (EN60721)	<95% r.h., no condensation
Operating temperature	-20 ~ +70 °C
Storage temperature	-20 ~ +80 °C

ISRW6-12..

ISRW6-12R

Wireless outdoor siren

See ISRW6-12.. for technical overview and note the additional / other specifications:

Colour	Red
--------	-----



S54538-F103-A200

ISRW6-12T

Wireless outdoor siren in orange

See ISRW6-12.. for technical overview and note the additional / other specifications:

Colour	Orange
--------	--------



S54538-F103-A300