

# Intrusion Detectors

## Internal Motion Detectors

### Wireless Detectors and Peripherals



**Type**

**Order No.**

**IWF6-10**

**Wireless flood detector, incl. battery**

**A5Q00020287**



The flood detector detects liquids (with electric conductivity) and enables the alarm system to detect water leaking (e.g. from the heating system, in the cellar, bathroom).

Area coverage	Sensor cable IP65 - max. 2 m
Identification	Unique ID serial number - 24 bit
Mounting and function test	Short the contact on sensor cable
Transmission output	Alarm, supervision, low battery
Battery	Lithium 3,6 V Type: XL-050F Size: 1/2AA
Frequency	868 MHz
Wireless module range	Up to 300 m in open space
Communication protocol	SiWay
Current consumption	Standby: 8 µA Max. 26 mA
Operating temperature	-10 ~ +50 °C
Storage temperature	-20 ~ +60 °C
Humidity (EN60721)	<85% r.h., no condensation
Housing protection (EN 60529)	IP41/ IK02
EMI rejection	Up to 2 GHz: >10 V/m
Dimensions (W x H x D)	27 x 124 x 28 mm
Weight	(incl. battery) 0.10 kg
Data sheet	A6V10098273

**IRCW6-11**

**Multifunctional remote control**

**S54543-F109-A100**



The Intrunet wireless multifunctional remote control in stylish white color is smaller than a credit card and only a few millimeters thick. Besides common functions such as set, unset and part set, the remote control includes a programmable key for user-defined functions as well as an emergency function (panic alarm). Furthermore, batteries can easily be exchanged for maximum product life duration.

Power supply	Rechargeable battery
Current consumption	Standby: <1 mA Max.: 28 mA
Battery	Lithium 3 V Type: CR2032
Frequency	868 MHz
Range	100 m at open space
Communication protocol	SiWay
Events	Set, unset, part set, optional: panic, control
Humidity (EN60721)	<85% r.h., no condensation
Housing protection (EN 60529)	IP41 / IK02
Operating temperature	-10 ~ +50 °C
Dimensions (W x H x D)	30 x 57 x 13 mm
Weight	0.01 kg
Data sheet	009093