

PAN AND TILTS : DC

P16 Series Medium Duty DC Pan & Tilt

DESCRIPTION

A robust and high performance DC Pan & Tilt unit. Allows reliable and accurate control of medium loads up to 16kg, with heavy-duty presets as standard. Includes pre-wired cables (2m long).

PRODUCT IMAGE



TECHNICAL INFORMATION

Dimensions	221 x 184 x 252 Topmount 380 x 184 x 230 Sidemount (Optional)
Unit Weight	7kg max.
Temperature Range	-20° C to +60° C (at 70% maximum duty cycle)
Environmental	IP67, BS EN 60 529
Power Consumption	2A max.
Power Supply	24V DC
Colour	Painted Polyester Powdercoat RAL7032 Leatherette Full Gloss
Load Weights	16kg Max
Pan Speed	48° /s Driving Torque 15Nm Holding Torque 20Nm
Tilt Seed	24° /s Driving Torque 20Nm Holding Torque 40Nm
Rotation	365° ± 2°

MTBF	Better than 10,000 hrs with <25% duty cycle
MTTR / MTTF	Better than 1 hour / Better than 10,000 hrs
Shock	30G Max. (packed)
Limit Switches	Better than 10,000,000 operations
Backlash	< ± 0.1°
Stall Protection	Permanent stall without damage
Max Tilt Rotation	+20° to -90° (side mount ±90°)
Camera Presets	Standard

