



PR500-Cotag Mullion proximity reader

Access Control

-
- Cotag proximity reader
 - Card read distance up to 30 cm with active card. Up to 10 cm with passive card.
 - Slim neat design

The PR500-Cotag is a compact proximity reader for SiPass access control system. It has a reading range of up to 30 cm with an active card and 10 cm with a passive card.

Technical data

PR500-Cotag	
Card technology	Cotag
Card read distance	Up to 30 cm with active card. Up to 10 cm with passive card.
Interface to controller	BC-Link, Clock&Data or Wiegand
Operating voltage	10.6 to 32 VDC
Current consumption	100 mA
Indicators	3 x LED (red/yellow/green) 1 x Buzzer
Environment	Indoor or outdoor use
Operating temperature	-30 to +50 °C
IP rating	IP 55
Housing	ABS base, clip-on ABS front cover
Colour	White
Dimensions (W x H x D)	40 x 140 x 18.5 mm
Keypad	no
Approval	CE

Details for ordering

Type	Part no	Designation	Weight
PR500-Cotag	S24246-F4706-A1	Mullion proximity reader	-

Issued by
Bewator AB
SE-171 24 Solna
Sweden

www.sbt.siemens.com

© 2008 Copyright by
Bewator AB, a Siemens company
Data and design subject to change without notice.
Supply subject to availability.

Document no. **A6V10207181**
Edition 04.2008