



BM3

Access Control

Door entry phone for PABX

-
- **Analog extension for the PABX system**
 - **Includes button for hotline function, CCTV control and tamper switch**

BM3 is used as an analog extension for the PABX internal tele phone system. It incorporates a built-in codelock with four codes. The BM3 also includes CCTV control and a tamper switch.

Connected telephone sets must be able to generate a standard tone signal (DTMF).

Technical data

BM3	
Interface	Two analog extension cables for PABX
Housing	Cast metal with stainless steel buttons and security lock. For flush mounting, use BB5 flush mounting kit.
Environment	Indoor or outdoor use. In very exposed locations, use SH3 or SH1 rain cover.
IP rating	IP54
Operating temperature	-35 to +50 °C. At 90% relative air humidity.
Operating voltage	12 to 24 VAC/DC
Current consumption	60 mA in standby
Dimensions (W x H x D)	80 x 200 x 40 mm
Calling time	1-99 seconds (can be extended x10)
Code capacity	4
Inputs	Exit button request with delay. Two inputs for disabling respective codes.
Outputs	Voltage-free relay contact, max. 2 A 28 VDC. Tamper switch for alarm (normally closed). Relay for control of CCTV system.
Opening time	1-99 seconds programmable from keypad (can be extended x10).

Details for ordering

Type	Part no	Designation	Weight
BM3	S24246-C7900-A1	Door entry phone for PABX	1.2 kg

Issued by
Bewator AB
SE-171 24 Solna
Sweden

www.sbt.siemens.com

© 2008 Copyright by
Bewator AB, a Siemens company
Data and design subject to change without notice.
Supply subject to availability.

Document no. **A6V10081708**
Edition 04.2008