



## BTK41

Access Control

## Door entry phone

- 
- Door phone with integrated codelock
  - Equipped with CCTV control, tamper switch and duress function
  - Sturdy construction for outdoor use

BTK41 is a traditional door phone with an integrated codelock. It connects by wire to one V801/B801 handset, and the A key is used for calling. It comes equipped with CCTV control, a tamper switch and a duress function.

## Technical data

---

<b>BTK41</b>	
Interface	5-wire cable to handset
Housing	Cast metal with stainless steel keys and security lock. For flush mounting, use BB5 flush mounting unit.
Colour	Grey
Environment	Indoor or outdoor use (IP54 design). In very exposed locations, use SH3 or SH1 rain cover.
IP rating	IP54
Operating temperature	-35 to +50 °C. At 90% relative air humidity.
Operating voltage	10 to 35 VAC/DC
Current consumption	40 mA in standby
Dimensions (W x H x D)	80 x 200 x 40 mm
Door capacity	1
Code capacity	Four 4-digit codes in standard mode (factory setting) Twenty 4-digit codes and ten 6-digit codes in advanced mode
Inputs	Exit button request with delay. Control of separate CCTV system. Two separate inputs for code disabling. External control of zero opening.
Outputs	Voltage-free relay contact, max. 2 A, 28 VDC. Open collector for duress. Open collector for door bell. Tamper switch for alarm connection (normally closed).
Opening time	1-99 seconds

## Details for ordering

---

Type	Part no	Designation	Weight
BTK41	S24246-F8005-A1	Door entry phone	1.3 kg

Issued by  
Bewator AB  
SE-171 24 Solna  
Sweden

[www.sbt.siemens.com](http://www.sbt.siemens.com)

© 2008 Copyright by  
Bewator AB, a Siemens company  
Data and design subject to change without notice.  
Supply subject to availability.

---

Document no. **A6V10081692**  
Edition 04.2008